

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-007-20297

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR D

8. Well No. **84**

9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other COALBED METHANE

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190 RATON, NM 87740

4. Well Location

Unit Letter C : 823.2 feet from the North line and 2442.2 feet from the West line

Section 10 Township 30N Range 18E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

7987' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐ **COMPLETION** ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

02/08/02 Halliburton ran Cement Bond Log. TOC at surface.

04/18/02 Halliburton perf'd 1st stage: 1212'-1214', 1237'-1239', 1258'-1260', 1278'-1280' 3 SPF 20 Holes

Halliburton frac'd 1st stage: Pumped 8.3 bbls HCL acid with 71,100 lbs of 16/30 Mesh Sand at 16 bpm, ATP at 1650 psi.

04/22/02 Halliburton perf'd 2nd stage: 1074'-1080' 3 SPF 17 Holes

Halliburton frac'd 2nd stage: Pumped 11.9 bbls HCL acid with 100,750 lbs of 16/30 Mesh Sand at 16.1 bpm, ATP at 1320 psi.

05/03/02 Installed rods, tubing, and pump. Well is ready to be put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm Specialist DATE 06/04/02

Type or print name: Shirley A. Mitchell Telephone No.: (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 6/7/02

Conditions of approval, if any: