

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-007-20306

5. Indicate Type of Lease
STATE FEE X
State Oil & Gas ☐ se No. ☒

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER X COALBED METHANE
b. Type of Completion:
NEW WORK PLUG DIFF. RESVR. OTHER
WELL ☒ OVER ☐ DEEPEN ☐ BACK ☐ RESVR. ☐ OTHER

7. Lease Name or Unit Agreement Name

VPR E

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

8. Well No.

12

3. Address of Operator

PO BOX 190
RATON, NEW MEXICO 87740

9. Pool name or Wildcat

Stubblefield Canyon Raton - Vermejo Gas

4. Well Location

Unit Letter D 1019.4 Feet From The North Line and 1091.6 Feet From The West Line

Section 04 Township 31N Range 19E NMPM COLFAX County

10. Date Spudded

02/13/02

11. Date T.D. Reached

02/14/02

12. Date Compl. (Ready to Prod.)

07/02/02

13. Elevations (DF& R(B. RT. GR. etc.)

8518'

14. Elev. Casinghead

8518'

15. Total Depth

2785'

16. Plug Back T.D.

2620'

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools
0 - TD

Cable Tools
None

19. Producing Interval(s) of this completion - Top, Bottom, Name
1088' - 2523' VERMEJO COALS

20. Was Directional Survey Made
No

21. Type Electric and Other Logs Run

Array Induction, Compensated Density, and Cement Bond Log.

21. Was Well Cored
No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24 lb.	302'	11"	90 sx.	None
5 1/2"	15.5 lb.	2747'	7 7/8"	370 sx.	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 7/8"	2544'	N/A

26. Perforations

2520' - 2523' 3 SPF, 8 Holes, 2446' - 2448' 3 SPF, 5 Holes
2310' - 2312' 3 SPF, 5 Holes, 2228' - 2230' 3 SPF, 5 Holes
1462' - 1464' 3 SPF, 5 Holes, 1420' - 1422' 3 SPF, 5 Holes, 1390' - 1392' 3 SPF, 5 Holes
1366' - 1368' 3 SPF, 5 Holes, 1345' - 1347' 3 SPF, 5 Holes, 1283' - 1286' 3 SPF, 8 Holes
1221' - 1223' 3 SPF, 5 Holes, 1232' - 1234' 3 SPF, 5 Holes, 1190' - 1193' 3 SPF, 8 Holes
1130' - 1132' 3 SPF, 5 Holes, 1088' - 1090' 3 SPF, 10 Holes, 1095' - 1097' 3 SPF, 10 Holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED
1088' - 2523' 242,430 lbs 16/30 mesh sand

28. PRODUCTION

Date First Production 07/05/02	Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/30-N-95 pc pump. Flowing gas up 5 1/2" casing.			Well Status (Prod. or Shut-in) Prod.		
Date of Test 07/05/02	Hours Tested 24 Hours	Choke Size Full 2"	Prod'n For Test Period N/A	Oil - Bbl N/A	Gas - MCF 35	Water - Bbl. 200
Flow Tubing Press	Casing Pressure 100 psi	Calculated 24-Hour Rate	Oil - Bbl. N/A	Gas - MCF 35	Water - Bbl. 200	Oil Gravity - API - (Corr.) N/A

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold, used for fuel

Test Witnessed By:

Gary Blundell

30. List Attachments

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature: Shirley Mitchell

Printed Name:

Shirley A. Mitchell

Title: Field Adm. Specialist

Date: 07/19/01

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____
T. Salt _____
B. Salt _____
T. Yates _____
T. 7 Rivers _____
T. Queen _____
T. Grayburg _____
T. San Andres _____
T. Glorieta _____
T. Paddock _____
T. Blinebry _____
T. Tubb _____
T. Drinkard _____
T. Abo _____
T. Wolfcamp _____
T. Penn _____
T. Cisco (Bough C) _____

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Delaware Sand _____
T. Bone Springs _____
T. _____
T. _____
T. _____
T. _____

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. Penn. "B" _____
 T. Penn. "C" _____
 T. Penn. "D" _____
 T. Leadville _____
 T. Madison _____
 T. Elbert _____
 T. McCracken _____
 T. Ignacio Otzte _____
 T. Granite _____
 T. Raton – Surface 440'
 T. Vermejo 2230'
 T. Trinidad 2532'
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____

OIL OR GAS SANDS
OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

No. 3, from to feet.

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology