

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Form C-101
Revised March 17, 1999

Oil Conservation Division
2040 South Pacheco
Santa Fe, NM 87505

Submit to appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address El Paso Energy Raton, L.L.C. P.O. Box 190 Raton, NM 87740		OGRID Number 180514
Property Code 24648		API Number 30-007- 20321
Property Name Vermejo Park Ranch (VPR)		Well No. VPR A-62

7 Surface Location									
U/I or Lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
C	10	34N	19E	C	1085.7'	NORTH	1360.4'	WEST	Coffey

8 Proposed Bottom Hole Location If Different From Surface									
U/I or Lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Proposed Pool 1 Vermejo					Proposed Pool 2 Raton				

Work Type Code N	Well Type Code G	Cable/Rotary ROTARY/AIR	Lease Type Code P	Ground Level Elevation 8384' (GL)
Multiple No	Proposed Depth 2,800'	Formation Trinidad	Contractor Not Available	Spud Date February 25, 2002

21 Proposed Casing and Cement Program					
Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
11"	8 5/8"	23#	330'	100 sx.	SURFACE
7 7/8"	5 1/2"	15.50#	2800'	300 sx.	SURFACE

22 Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

- Drill 11" hole to +/- 330' with air
- Set 8 5/8" surface casing and cement to surface with 100 sks of cement.
- Drill 7 7/8" hole to 2,800' with air. Run open hole logs.
- Set 5 1/2" production casing to TD and cement to surface. Cement volumes calculated from open hole logs.
- Perforate and stimulate Vermejo and/or Raton Coals. Clean out wellbore and run production equipment.

23 I hereby certify that the information given above is true and complete to the best of my knowledge and belief. Signature: <i>DR Lankford</i>		OIL CONSERVATION DIVISION Approved by: <i>[Signature]</i>	
Printed name: Donald R. Lankford		Title: DISTRICT SUPERVISOR	
Title: Senior Petroleum Engineer		Approval Date: 1/29/02	Expiration Date: 1/29/03
Date: 01-23-02	Phone: (505) 445-6721	Conditions of Approval: Attached ☐	