

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-007-20329
5. Indicate Type of Lease STATE ☐ FEE ☒
State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER _____			7. Lease Name or Unit Agreement Name VPR A		
b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER _____					
2. Name of Operator EL PASO ENERGY RATON, L.L.C.			8. Well No. 77		
3. Address of Operator P.O. BOX 190, RATON, NEW MEXICO 87740			9. Pool name or Wildcat Stubblefield Canyon Raton - Vermejo Gas		
4. Well Location Unit Letter <u>G</u> <u>1658.2</u> Feet From The <u>North</u> Line and <u>1581.0</u> Feet From The <u>East</u> Line Section <u>10</u> Township <u>31N</u> Range <u>19E</u> NMPM Colfax County					
10. Date Spudded 02/02/02	11. Date T.D. Reached 02/23/02	12. Date Compl. (Ready to Prod.) 05/02/02	13. Elevations (DF& R(B, RT, GR, etc.) 8372' (GL)	14. Elev. Casinghead 8372'	
15. Total Depth 2717'	16. Plug Back T.D. 2620'	17. If Multiple Compl. How Many Zones? 	18. Intervals Drilled By 0 - TD	Rotary Tools Cable Tools NONE	
19. Producing Interval(s), of this completion - Top, Bottom, Name 977' - 2478' Vermejo Coals				20. Was Directional Survey Made NO	
21. Type Electric and Other Logs Run Epithermal Neutron Litho Density, Array Induction Linear Correlation, and Acoustic Cement Bond Log				22. Was Well Cored No	

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	303'	11"	85 sx	None
5 1/2"	15.5	2651'	7 7/8"	351 sx	
24. LINER RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	
26. Perforation record (interval, size, and number)			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.		
2474' - 2478' 3 SPF 12 Holes			DEPTH INTERVAL		
2374' - 2376', 2409' - 2411' Shot 3 SPF 12 Holes			AMOUNT AND KIND MATERIAL USED		
2230' - 2232', 2269' - 2276' Shot 3 SPF 27 Holes			977' - 2478'		
2041' - 2043', 2046' - 2048' Shot 3 SPF 12 Holes			204,500 lbs of 16/30 Brady Sand		
1202' - 1207', 1233' - 1235', 1236' - 1238', 1241' - 1243' Shot 3 SPF 33 Holes					
977' - 979', 1011' - 1013', 1042' - 1044', 1051' - 1053', 1070' - 1072' Shot 3 SPF 30 Holes					

28. PRODUCTION							
Date First Production 05/04/02		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/40-N-95 PC Pump. Flowing gas up 5 1/2" Casing.				Well Status (Prod. or Shut-in) Prod.	
Date of Test 05/04/02	Hours Tested 24 hrs	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 7	Water - Bbl. 163	Gas - Oil Ratio N/A
Flow Tubing Press.	Casing Pressure 20 psi	Calculated 24-Hour Rate	Oil - Bbl N/A	Gas - MCF 7	Water - Bbl. 214	Oil Gravity - API - (Corr.) N/A	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel.	Test Witnessed By: Gary Blundell
--	-------------------------------------

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.

Signature: Shirley A. Fritchell Printed Shirley A. Mitchell Title Field Adm Specialist Date: 06/14/02

his form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or re-perforated well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in triplicate except on state land, where six copies are required. See Rule 1105.

Southeastern New Mexico		Northwestern New Mexico	
Ashy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
Yates	T. Miss	T. Cliff House	T. Leadville
Rivers	T. Devonian	T. Menefee	T. Madison
Green	T. Silurian	T. Point Lookout	T. Elbert
Grayburg	T. Montoya	T. Mancos	T. McCracken
San Andres	T. Simpson	T. Gallup	T. Ignacio Ozite
Gorteta	T. McKee	Base Greenhorn	T. Granite
Pad dock	T. Ellenburger	T. Dakota	T. Raton Top - 344'
Emebry	T. Gr. Wash	T. Morrison	T. Vermajo - 2,220'
Tabb	T. Delaware Sand	T. Todilto	Trinidad 2,490'
Drinkard	T. Bone Springs	T. Entrada	T.
Libo	T.	T. Wingate	T.
Wolcamp	T.	T. Chinle	T.
Penn	T.	T. Permian	T.
Cisco (Bough C)	T.	T. Penn "A"	T.

include data on rate of water inflow and elevation to which water rose in hole.

to	feet
1. from	
2. from	
3. from	

(Attach additional sheet if necessary)

[illegible]