

District I

1625 N French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

Corrected Copy

WELL API NO.

30-007-20336

5. Indicate Type of Lease

STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER _____

b. Type of Completion:

NEW ☒ WORK ☐ PLUG ☐ DIFF. ☐
WELL OVER ☐ DEEPEN ☐ BACK ☐ RESVR. OTHER AMENDED

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190, RATON, NEW MEXICO 87740

4. Well Location

Unit Letter E; 1863.0 Feet From The North Line and 1068.2 Feet From The West LineSection 12 Township 31N Range 19E NMPM Colfax County

10. Date Spudded

03/16/02

11. Date T.D. Reached

03/17/02

12. Date Compl. (Ready to Prod.)

05/06/02

13. Elevations (DF& R(B. RT, GR, etc.)

8292' (GL)

14. Elev. Casinghead

8292'

15. Total Depth

2635'

16. Plug Back T.D.

2535'

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools

0 - TD

Cable Tools

NONE

19. Producing Interval(s), of this completion - Top, Bottom, Name

911' - 2387' Vermejo Coals

20. Was Directional Survey Made

NO

21. Type Electric and Other Logs Run

Mud Log, Epithermal Neutron Litho Density, Array Induction Linear Correlation, and Acoustic Cement Bond Log

22. Was Well Cored
No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	324'	11"	100 sx	None
5 1/2"	15.5	2554'	7 7/8"	357 sx	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 7/8"	2535'	No

26.
2345' - 2347', 2385' - 2387' Shot 3 SPF 10 Holes
2196' - 2198', 2233' - 2235', 2297' - 2299' Shot 3 SPF 15 Holes Vermejo Coals
1897' - 1899', 1943' - 1945', 1981' - 1983' Shot 3 SPF 15 Holes
1095' - 1097', 1106' - 1108', 1156' - 1158', 1204' - 1206' Shot 3 SPF 15 Holes
1020' - 1022', 1027' - 1029', 1032' - 1034' Shot 3 SPF 15 Holes
911' - 913', 951' - 953', 954' - 956', 983' - 985' Shot 3 SPF 20 Holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
911' - 2387'	330,290 lbs of 16/30 Brady Sand

28. PRODUCTION

Date First Production 05/10/02		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/30-N-95 PC Pump. Flowing gas up 5 1/2" Casing			Well Status (Prod. or Shut-in) Prod.		
Date of Test 05/10/02	Hours Tested 24 hrs.	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 45	Water - Bbl. 257	Gas - Oil Ratio N/A
Flow Tubing Press.	Casing Pressure 130 psi	Calculated 24- Hour Rate	Oil - Bbl. N/A	Gas - MCF 45	Water - Bbl. 257	Oil Gravity - API - (Corr.) N/A	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold, used for fuel.

Test Witnessed By:
Gary Blundell

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.

Signature: *Shirley Mitchell* Printed Shirley A. Mitchell Title Field Adm Specialist Date: 08/20/02

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

Southeastern New Mexico

Southeastern New Mexico

Northwestern New Mexico

T. Anyh	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Ortiz
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T. Raton Top - 370'
T. Blinebry	T. Gr. Wash	T. Morrison	T. Vermajo - 2,152'
T. Tubb	T. Delaware Sand	T. Todillo	T. Trinidad 2,409'
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

include data on rate of water inflow and elevation to which water rose in hole.

IMPORTANT WATER SANDS

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet

LITHOLOGY RECORD

(Attach additional sheet if necessary)

[illegible]