

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

WELL API NO. 30-007-20340

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR A

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other COALBED METHANE

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

8. Well No. 82

3. Address of Operator

P.O. BOX 190 RATON, NM 87740

9. Pool name or Wildcat

4. Well Location

Unit Letter K : 1441.3 feet from the South line and 1512.1 feet from the West line
Section 33 Township 32N Range 20E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
8090' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☒ COMPLETION

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

05/16/02 HES ran cement bond log. TOC at 20'.

06/25/02 HES perf'd 1st stage: 2221'-2223' 3 SPF 15 Holes

HES frac'd 1st stage: Pumped 2.4 bbls HCL acid with 1,000 lbs of 16/30 Brady sand at 5.1 bpm, ATP 2685 psi, ISIP 3250 psi.

HES perf'd 2nd stage: 2169'-2171', 2176'-2178' 3 SPF 10 Holes

HES frac'd 2nd stage: Pumped 2.4 bbls HCL acid with 61,400 lbs of 16/30 Brady sand at 8.9 bpm, ATP 2090 psi, ISIP 245 psi.

HES perf'd 3rd stage: 2062'-2064' 3 SPF 5 Holes

HES frac'd 3rd stage: Pumped 2.4 bbls HCL acid with 11,500 lbs of 16/30 Brady sand at 7.1 bpm, ATP 2087 psi, ISIP 300 psi.

HES perf'd 4th stage: 1997'-1999' 3 SPF 5 Holes

HES frac'd 4th stage: Pumped 2.4 bbls HCL acid with 2,100 lbs of 16/30 Brady sand at 5.1 bpm, ATP 3852 psi, ISIP 2600 psi.

HES perf'd 5th stage: 1265'-1267' 3 SPF 5 Holes

HES frac'd 5th stage: Pumped 2.4 bbls HCL acid with 11,600 lbs of 16/30 Brady sand at 8.8 bpm, ATP 3215 psi, ISIP 815 psi.

06/29/02 Installed rods, tubing, and pump. Well is ready to be put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm. Specialist DATE 08/15/02
Type or print name: Shirley A. Mitchell Telephone No.: (505) 445-6785

(This space for State use)
APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 8/21/02
Conditions of approval, if any: