

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

WELL API NO.

30-007-20370

5. Indicate Type of Lease

STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER _____

b. Type of Completion:

NEW ☒ WORK ☐ PLUG ☐ DIFF.
WELL OVER ☐ DEEPEN ☐ BACK ☐ RESVR. OTHER _____

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190, RATON, NEW MEXICO 87740

7. Lease Name or Unit Agreement Name

VPR C

8. Well No.

96

9. Pool name or Wildcat

Stubblefield Canyon Raton - Vermejo Gas

4. Well Location

Unit Letter C : 774 Feet From The North Line and 1974 Feet From The West Line

Section 30 Township 32N Range 21E NMPM Colfax County

10. Date Spudded 01/21/03 11. Date T.D. Reached 01/22/03 12. Date Compl. (Ready to Prod.) 04/08/03 13. Elevations (DF& R(B. RT, GR, etc.) 7687' (GL) 14. Elev. Casinghead 7687'

15. Total Depth 2095' 16. Plug Back T.D. 2061' 17. If Multiple Compl. How Many Zones? 18. Intervals Drilled By 0 - TD 19. Producing Interval(s), of this completion - Top, Bottom, Name 1043' - 1848' Vermejo - Raton Coals 20. Was Directional Survey Made NO

21. Type Electric and Other Logs Run Epithermal Neutron Litho Density, Array Induction Linear Correlation, Gamma Ray, Caliper, CCL, Mud Log, and Acoustic Cement Bond Log 22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	325'	11"	100 sx	None
5 1/2"	15.5	2071'	7 7/8"	295 sx	

24. LINER RECORD				25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET
					2 7/8"	1886'

26. Perforation record (interval, size, and number)		27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
1845' - 1848' 3 SPF 8 Holes (5' of coal)		DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
1803' - 1805' 3 SPF 5 Holes (1' of coal)		1043' - 1848'	114,560 lbs of 20/40 Ottawa Sand
1693' - 1695' 3 SPF 5 Holes (3' of coal)			
1658' - 1660' 3 SPF 5 Holes (1' of coal)			
1090' - 1092' 3 SPF 5 Holes (2' of coal)			

PRODUCTION

28. Date First Production 04/22/03		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/30-N-95 PC Pump. Flowing gas up 5 1/2" Casing.			Well Status (Prod. or Shut-in) Prod.	
Date of Test 04/22/03	Hours Tested 24 hrs.	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 75	Water - Bbl. 342
Flow Tubing Press.	Casing Pressure 50	Calculated 24-Hour Rate	Oil - Bbl. N/A	Gas - MCF 75	Water - Bbl. 342	Oil Gravity - API - (Corr.) N/A

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel. Test Witnessed By: Jerry Colburn

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.

Signature: Shirley A. Mitchell Printed Shirley A. Mitchell Title Field Adm Specialist Date: 04-30-03

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn
B. Salt	T. Atoka
T. Yates	T. Miss
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres	T. Simpson
T. Glorieta	T. McKee
T. Paddock	T. Ellenburger
T. Blinbry	T. Gr. Wash

T. Tubb _____	T. Delaware Sand _____
T. Drinkard _____	T. Bone Springs _____
T. Abo _____	T. _____
T. Wolfcamp _____	T. _____
T. Penn _____	T. _____
T. Cisco (Bough C) _____	T. _____

Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzte _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. Raton Top – 0' _____
T. Morrison _____	T. Vermejo – 1,641' _____

T. Todilto	T. _____
T. Entrada	T. _____
T. Wingate	T. _____
T. Chinle	T. _____
T. Permian	T. _____
T. Penn "A"	T. _____

OIL OR GAS SANDS
OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology