

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Hunt Oil Company

3. ADDRESS OF OPERATOR
2900 First Nat'l Bank Bldg., Dallas, TX 75202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: 5639'

5. LEASE
NM 26516

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-

7. UNIT AGREEMENT NAME
-

8. FARM OR LEASE NAME
Puerto Creek Federal

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 28-7N-21E

12. COUNTY OR PARISH
Guadalupe

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5056' GL, 5067' DF, 5068' KB

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Set production casing (5-1/2")	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-23-82: Ran 152 JTS 5-1/2", 14#, K-55 casing set at 5638' and cemented with 1,600 sx 50-50 Class C-Pozmix A, 2% Gel, 6# Salt/sx, 0.4% Halad-4, 0.3% CFR-2, 1/4# Flocele/sx. Circulated 50 sx to surface.

RECEIVED

AUG 26 1982

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____ N/A Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED William J. Boyle TITLE Engineer DATE 8-23-82

ACCEPTED FOR RECORD
(This space for Federal or State office use)
(ORIG. SGD.) DAVID R. GLASS

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

OCT 12 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO
See Instructions on Reverse Side

