

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L 6331

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CELEBRATE OR PLUG BACK. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PURPOSES.)

1. OIL ☒ GAS ☐ OTHER ☐		RECEIVED JAN - 5 1984 OIL CONSERVATION DIVISION SANTA FE	7. Unit Agreement Name
2. Name of Operator Rio Petro., Ltd.			8. Farm or Lease Name
3. Address of Operator 4835 LBJ Freeway, Suite 635, Dallas TX 75234			9. Well No. 16
4. Location of Well UNIT LETTER <u>O</u> <u>810</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>15</u> TOWNSHIP <u>11N</u> RANGE <u>25E</u> NMPM.			10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4585.0' GL		12. County Guadalupe	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 12:00 P.M. on December 1, 1983. Drilled 14 3/4" hole to 36' TD. Ran 36' of 13 3/8" 48# casing and cemented with 14 sacks of neat cement from TD to surface. Drilled 12 1/4" hole to 540 ft. and ran 533' of 8 5/8" 23# casing to shut off water at 455'. Drilled 7 7/8" hole to 1180' TD. Attempted to pull casing but string parted in first collar 40' beneath surface. Received permission to plug well from Mr. Roy Johnson December 8, 1983. His instructions were to set 25 sack cement plug at TD, 25 sack cement plug from 20' below top of San Andres and run 1" line in casing annulus to 380' and cement back to surface. Well was plugged as follows: 35 sacks set from 1058' to 1180', 25 sacks from 667' to 754' and 172 sacks in annulus from surface to 380'. Finished plugging operations at 9:00 P.M. Dec. 8, 1983. Ran Litho density log and cored well from 619' to 736'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Charles C Joy</u>	TITLE <u>Agent</u>	DATE <u>12-27-83</u>
APPROVED BY <u>Roy E Johnson</u>	TITLE <u></u>	DATE <u>1/5/84</u>
CONDITIONS OF APPROVAL, IF ANY:		