

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1930, Hobbs, NM 88240

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.  
30-019-20096

5. Indicate Type of Lease  
STATE  FEE

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS)

7. Lease Name or Unit Agreement Name  
STATE MR. JONES 32 NO.1

1. Type of Well:  
OIL WELL  GAS WELL  OTHER

8. Well No. 1

2. Name of Operator  
LABRADOR OIL COMPANY

9. Pool name or Wildcat  
WILDCAT

3. Address of Operator  
400 NORTH ST. PAUL, SUITE 400, DALLAS TEXAS 75201

4. Well Location  
Unit Letter F : 1795 Feet From The NORTH Line and 1895 Feet From The WEST Line  
Section 32 Township 7N Range 23E NMPM SENW County

10. Elevation (Show whether DF, RKB, RT, GR, etc)  
GROUND-4642'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:  
PERFORM REMEDIAL WORK  PLUG AND ABANDON  REMEDIAL WORK  ALTERING CASING   
TEMPORARILY ABANDON  CHANGE PLANS  COMMENCE DRILLING OPNS.  PLUG AND ABANDONMENT   
PULL OR ALTER CASING  CASING TEST AND CEMENT JOB   
OTHER:  OTHER:

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

DRILL 12-14" HOLE TO RKB 2889.' RAN 47 JTS N-80 47LB 9-5/8" CASING PLUS 26 JTS OF 47. I  
P-110 CAING BUTRESS TREAD. TOTAL LENGTH OF STRILG2885.76 PLUS FS AND FC2.75 OR TOTAL  
OF 2888.51'. LAND CASING W/SHOE AT 2886. RKB FC AT 2804.39' CEMENT WITH 750 SAKS OF 35/65  
COZ H 12.4 PPG, TAIL WITH 300 SAKS C AT 14.8 PPG, DISPLACE WITH 205 BBLs WATER, BUMP  
PLUG WITH 1200 PSI. FLOAT HELD CIP 4 HRS RELEASE AT 5 am 9-30-94 RECOVERED 161 SAKS AT  
SURFACE-WOC 20 HRS. NIPPLE UP-RUND IN AND TAG CEMENT 2821' DRILL TO SHOE AT 2882'  
CLOSE DRAMS AND PRESSURE UP TO 1300 PSI FOR 30 MIN.NO LOSS-DRILL SHOE AND I JT.  
TEST SEAT AND FORMATION WITH EQUIVILANT 13 LBS MUD NO BREAKDOWN- DRILL ON

I hereby certify that the information above is true and complete to the best of my knowledge and belief.  
SIGNATURE Billy N. Johnson TITLE COMPANY MAN DATE 6-4-94  
TYPE OR PRINT NAME BILLY N. JOHNSON TELEPHONE NO. 214-955-918

(This space for State Use)  
APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 11-8-94  
CONDITIONS OF APPROVAL, IF ANY: