



JAN 10 1955

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office N. Mex.
Lease No. 06677
Unit _____

JAN 17 11 0:59 AM

RECEIVED

JAN 10 1955

SUNDRY NOTICES AND REPORTS ON WELLS

S. GEOLOGICAL SURVEY
ROSEMBO, NEW MEXICO

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	☒
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	☐
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	☐
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	☐
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	☐
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	☐
NOTICE OF INTENTION TO ABANDON WELL.....		☐

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. I is located 660 ft. from [N] line and 660 ft. from [E] line of sec. 3
S.E.S.E. 8N. 18E.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Guadalupe N. Mex.
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5500 est. ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

I2-31-54: Spudded-Drilled 11" hole to 256'. Reamed to 17 1/2" to 215'.

I-3-55: Ran 6 Jts. 13 5/8" O.D. 36# Armco Spiral Casing. Set at 215' R.D.B. Cemented by Halliburton with 200 sac Reg. Cement, 190# Calcium Chloride. Cement circulated 30' left in pipe. Cement set 24 hours.

I-4-55: Close B.C.P. and pressure to 400 P.S.I. for 30 minutes. Holding-To drill ahead.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Sunray Oil Corp.

Address Santa Rosa N. Mex.
570 Tower Hotel

By E. J. [Signature]

Title Group Foreman