

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.	30-021-20113
5. Indicate Type of Lease	STATE ☐ FEE ☒
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	BDCDGU-1933
8. Well No.	111
9. Pool name or Wildcat	Tubb

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☐ GAS WELL ☐ OTHER ☒ C02	
2. Name of Operator Amoco Production Company	
3. Address of Operator PO Box 606, Clayton, NM 88415	
4. Well Location Unit Letter <u>G</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>East</u> Line Section <u>11</u> Township <u>19N</u> Range <u>33E</u> NMMPM Harding County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4965' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: <u>Install Casing Liner</u> ☒	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRUSU
RUN & SET 1.625" BLANKING PLG IN PROFILE
BLEED TBG TO 0 PSI
NUBOP
RELEASE ON/OFF TOOL
SWAB CSG DOWN, REC AS MUCH FLUID AS POSSIBLE
LAYDOWN FG TBG
RUN POLYBORE GAUGE RING
OPTION #1
IF GAUGE RING GOES & LOOKS OK WHEN PULLED:
RUN 10-3 1/8" DRILL COLLARS (COLLARS EQUIPPED
WITH 2 7/8" PAC BOX ON TOP); RIG UP ROLLER
REDUCTION

UNIT; RUN POLY LINER TO TOP OF PKR; FISH DRILL
COLLARS FROM POLYLINER W/TBG FUSE ON
WELLHEAD FLANGE; INSTALL SS B-1 ADAPTER &
MASTER VALVE; INSTALL METER RUN; RU
LUBRICATOR & FISH BLANKING PLUG; RETURN
WELL TO PRODUCTION; RDMOSU
OPTION #2
IF GAUGE RING DOES NOT MAKE IT TO PKR DEPTH
OR COMES OUT WITH SIGNS OF CSG DAMAGE,
RERUN 3 1/2" FG PRODUCTION TBG; LATCH ON TO
PKR; FISH BLANKING PLUG; PRESS TEST CSG & PKR
TO 500 PSI; RETURN WELL TO PRODUCTION;
RDMOSU

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Billy E. Prichard TITLE Field Foreman DATE 2/27/97
TYPE OR PRINT NAME Billy E. Prichard TELEPHONE NO. 374-3053

(This space for State Use)

APPROVED BY Ry E. Prichard DISTRICT SUPERVISOR DATE 3/17/97
CONDITIONS OF APPROVAL, IF ANY: