

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All test reported shall be measured by the in the case of directionally drilled wells, true vertical depths shall also be reported. For multiple correlations, Items 33 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1155.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
T. Salt _____
B. Salt _____
T. Yates _____
T. 7 Rivers _____
T. Queen _____
T. Grayburg _____
T. San Andres 1292
T. Glorieta 1516
T. Paddock _____
T. Blinbry _____
T. Tubb 2070
T. Drinkard _____
T. Abo _____
T. Wolfcamp _____
T. Penn. _____
T. Cisco (Bough C) _____
T. Granite 2182

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn. "A" _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
No. 2, from _____ to _____
No. 3, from _____ to _____
No. 4, from _____ to _____
No. 5, from _____ to _____
No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	524	524	Surf. Rock & Red Beds				
524	1265	741	Red Beds & Shale				
1265	2170	905	Sand, Shale & Anhy.				
2170	2343	173	Sand, Shale & Granite				
			T.D. 2343'				