

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

3a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L-5817

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- CO ₂ supply	7. Unit Agreement Name
2. Name of Operator Cities Service Company	8. Farm or Lease Name STATE DD
3. Address of Operator Box 1919, Midland, TX 79702	9. Well No. 1
4. Location of Well UNIT LETTER <u>K</u> 1980 FEET FROM THE <u>South</u> LINE AND 1980 FEET FROM THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>19N</u> RANGE <u>29E</u> NMPM.	10. Field and Pool, or Wildcat Bravo Dome Area
15. Elevation (Show whether DF, RT, GR, etc.) 4482.6' GR	12. County Harding

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☒
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOB ☒
OTHER ☐	OTHER ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 2250' Granite. Waiting on completion unit. MIRU rotary & spudded a 12½" hole @ 2200 MST on 3/22/81 & drld to a T.D. of 601' in Red Beds. Ran & set 15 Jts(590') 8-5/8" OD 24# K55 csg @ 600' & cmtd w/500 sacks Class H w/2% CaCl₂ cmt. Plug down @ 805 MST on 3/24/81. Bumped plug w/800# - ok. Cmt circulated to surface. NMOCD was notified but did not witness. WOC 18 Hrs. Drld a 7-7/8" hole to a T.D. of 2250' in Granite. Ran & set 52 Jts (2233') 5½" OD 14# K55 csg @ 2243' & cmt w/700 sacks Class H w/ 2% Gel, 5% KCl, 2% CaCl₂, 0.4 of 1% Halad, 5# Gilsonite & ¼# Flocele/sack cmt. Plug down @ 0800 MST on 3/29/81. Bumped plug w/750# - ok. NMOCD was notified but did not witness. Cmt circulated to surface. ND BOP. Set slips, CO csg & install well head.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. P. Miller TITLE Region Oper. Mgr. DATE 4/1/81

APPROVED BY Carl Ulvog TITLE SENIOR PETROLEUM GEOLOGIST DATE 4/6/81

CONDITIONS OF APPROVAL, IF ANY: