

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-101
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API # 30-021-20220

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

5A. Indicate type of Lease
STATE ☐ FEE ☒
5. State Oil & Gas Lease No.

1a. Type of work b. Type of Well OIL WELL ☐ GAS WELL ☒ CO2 ☐ OTHER ☐		DRILL ☒ DEEPEN ☐ PLUG BACK ☐		Bravo Dome Carbon Dioxide Gas Unit	
2. Name of Operator Amoco Production Company		SINGLE ZONE ☒ MULTIPLE ZONE ☐		Bravo Dome Carbon Dioxide Gas Unit	
3. Address of Operator P.O. Box 68 Hobbs, New Mexico 88240				9. Well No. 1833 051F	
4. Location of well UNIT LETTER <u>F</u> LOCATED <u>1650</u> FEET FROM THE <u>North</u> LINE <u>1650</u> FEET FROM THE <u>West</u> LINE OF SEC. <u>5</u> TWP. <u>18N</u> SEC. <u>33E</u> RANGE <u>10W</u>				Bravo Dome Carbon Dioxide Gas Unit 640-Acre Area	
				17. County <u>Harding</u>	
19. Proposed Depth 2900'		15A. Formation Tubb		20. Method of C.T. Rotary	
21A. Kind & Status Plug. Bond Blanket-on-file		21B. Drilling Contractor N/A		22. Approx. Date work will start ASAP	
1. Elevations (show whether Dr., H.I., etc.) 4766' GL					

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
12-1/4"	9-5/8"	32.30#	700'	Circulate	surface
8-3/4"	7"	20.0#	2900'	Tieback to 9-5/8"	surface

Propose to drill and equip well in the Tubb formation. After reaching TD logs will be run and evaluated. Perforate and stimulate as necessary in attempting commercial production.

Mud Program: 0 - 700' Native Spud Mud
700 - TD KCL Salt Water Gel-Starch

BOP Diagram attached.

0+5-NMOCD, SF 1-J. R. Barnettt, HOU Rm. 21.156 1-F. J. Nash, HOU Rm. 4.206 1-WF, C 1-WF, 1-Susp, 1-CMH 1-Amerada 1-Amerigas 1-Cities Service 1-Conoco 1-CO2 in Action 1-Sun 1-Excelsior 1-Tex 1-Exxon

ABOVE SPACE DESCRIBE PROPOSED PROGRAM; IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROD. ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

C. Herring Title Administrative Analyst (SG) Date 9/26/85

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 10-2-85

APPROVAL VALUE FOR 180 DAYS
PERMIT NUMBER 4-2-86
UNLESS DRILLING OTHERWISE

**NEW MEXICO OIL CONSERVATION COMMISSION
WELL LOCATION AND ACREAGE DEDICATION PLAT**

Form C-102
Supersedes C-128
Effective 1-1-65

All distances must be from the outer boundaries of the Section.

Operator AMOCO PRODUCTION COMPANY			Lease B.D.C.D.G.U.		Well No. 1833 051F
Unit Letter F	Section 5	Township T18N	Range R33E	County HARDING	
Actual Footage Location of Well: 1650 feet from the NORTH line and 1650 feet from the WEST line					
Ground Level Elev. 4766	Producing Formation Tubb	Pool Bravo Dome 640 Acre Area		Dedicated Acreage: 640 Acres	

1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☒ Yes ☐ No If answer is "yes," type of consolidation Agreement or Forced Pooling

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) _____

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.


TR 56 Amerada Hess Corp. Amoco Production Co. Sun Production Co. Bobby Adee Federal Land Bank of Wichita 1650	TR 609 Johnanne Adee Sun Production Co. Amerada Hess Corp. Johnanne Adee Lucille A. Muse Gary L. Bennet, et al


CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Name: [Signature]
 Position: Admin. Analyst (SG)
 Company: Amoco Production Company
 Date: 9-26-85

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

SEP 26 1985
 Date Surveyed

 Registered Professional Engineer
 and/or Land Surveyor
 N.M. 5103
 Certificate No. E. SHIELDS



STANDARD 2000 PSI W.P. BOP STACK

1. Blow-out preventers may be manually operated.
2. All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
3. Bell nipple above blow-out preventer shall be same size as casing being drilled through.
4. Kelly cock to be installed on kelly.
5. Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
6. Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
7. Double or space saver type preventers may be used in lieu of two single preventers.
8. BOP rams to be installed as follows:
 - Top preventer - Drill pipe or casing rams
 - Bottom preventer - Blind rams

*Amoco District Superintendent may reverse location of rams.
9. Extensions and hand wheels to be installed and braced at all times.
10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

