

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation

E. C. BARNHOLT

PETROLEUM ENGINEER

~~XX~~

DENVER, COLORADO 80202

OFFICE 303/222-0050

903 Republic Building

HOME 303/733-1120

BROOKS EXPLORATION, INC.

WELL SUMMARY

STATE: New Mexico
COUNTY: Mora
LEASE: Berlier
WELL NO.: 1
LOCATION: SW/4 Section 14, Township 21 North, Range 21 East
DATE SPUDDED: September 16, 1975
ELEVATION: 6178 ft.
CONDUCTOR HOLE SIZE: 13-3/4" DEPTH: 41 ft.
CONDUCTOR SIZE: 10-3/4" Amount: 40 ft.
SIZE HOLE BELOW CONDUCTOR: 8-3/4" to 327 ft.
PRODUCTION CASING SIZE: 7" to 326 ft.
CEMENTED WITH: 50 sacks cement didn't circulate
STIMULATION: None, well is plugged and abandoned

DAILY DRILLING REPORT

September 16, 1975: Spud well at 12:10 P.M. Drilled 6-1/2" pilot hole to 41 ft., reamed pilot hole to 13-3/4". Set conductor at 40 ft.
September 17, 1975: Drilled 8-3/4" hole to 327 ft., started running 7" casing.
September 18, 1975: Finished running 7" casing to 326 ft.
September 20, 1975: Cemented with 50 sacks, cement displaced at 2:20 P.M.

September 22, 1975: Rig up drilling rig, stuck in mud due to heavy rains, get J. D. Schmidt cat to spot rig. Run in with drill pipe and bit, only 20 ft. of watery cement.

September 23, 1975: Drilled 6-1/8" hole to 459 ft. T.D. Pulled drill pipe and bit, noticed moisture on last five joints of drill pipe, went back in hole, blew well for 1-1/2 hrs. Moisture returns from 7" casing and 7" X 10-3/4" annulus. Suspect bad cement job.

September 25, 1975: Set open hole bridge plug at 329 ft., set cement plug on top of B.D. with dump bailer. Shut in.

September 27, 1975: Attempt to run 3/4" pipe beside 7" casing, would only go to 40 ft. Rigged up drilling rig, recemented through drill pipe with 15 sacks, 3 bbl. water ahead of cement, 5 bbls. water behind. Shut in.

September 28, 1975: WOC

September 29, 1975: Ran bit and drill pipe. Water at 348 ft., top cement 400 ft., blew well for 1-1/2 hrs., making water 1-2 GPM.

October 9, 1975: Rigged up drilling rig, ran drill pipe to bottom. Plugged well from 400 ft. to 288 ft. with 16 sacks. Pulled conductor and one joint of 7", used 10 sack top plug. P&A.