

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	☒
U.S.O.B.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 12-1-77

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN UP PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT TO DRILL FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER	2. Name of Operator AMOCO PRODUCTION COMPANY	3. Address of Operator P. O. Box 68, Hobbs, New Mexico 88240	4. Location of well projected C 150 North 1630 Lat 36°00' 01.187" Long 105°07' 39.236" West LINE, SECTION 3 TOWNSHIP 20-N RANGE 17-E	5. Indicate Type of Lease State ☐ Fee ☒	6. State Oil & Gas Lease No.	7. Unit Agreement Name	8. Name of Lease Name Salman Ranch A	9. Well No. 1	10. Field and Pool, or Wildcat Wildcat	11. Elevation (Show whether DF, RT, Glt, etc.) 7323.9' GR	12. County Mora
--	---	---	---	---	------------------------------	------------------------	---	------------------	---	--	--------------------

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING CONS. ☐
CASING TEST AND CEMENT JOBS ☒
OTHER spud ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 8-20-84 drilled to TD of 40' and set 20", 52.73# conductor pipe. Conductor set at 40' and cemented with 2-3/4 yard redi-mix. Sharp rig #48 spud with a 17.5' bit and drilled to a TD of 502'. On 8-26-84 set 13-3/8" 54.5#, J-55 casing. Casing set at 502'. Cemented with 200 sx class C with additives, 200 sx class C thixset with additives, and tailed-in with 200 sx C with additives. Plug down 12:15 pm 8-26-84, circulated out 225 sx. WOC 18 hours, tested casing to 700 psi for 30 min, tested OK. Reduced bit to 12-1/4" and resumed drilling.

0+5-NMOCD,SF 1-J. R. Barnett, HOU 21.156 1-F. J. Nash, HOU Rm. 4.206 1-GCC

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Harry C. Clark

TITLE Assist. Admin. Analyst

DATE 8-30-84

APPROVED BY [Signature]

TITLE DISTRICT SUPERVISOR

DATE 9-4-84

CONDITIONS OF APPROVAL, IF ANY: