

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL GAS WELL OTHER

Name of Operator
Yates Petroleum Corporation

Address of Operator
207 South 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER L 2310 FEET FROM THE South LINE AND 660 FEET FROM
THE West LINE, SECTION 12 TOWNSHIP 10N RANGE 27E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name
T-4 Filly's Tooth

9. Well No.
1

10. Field and Pool, or Wildcat
Undes. Penn

15. Elevation (Show whether DF, RT, GR, etc.)
4300' GR

12. County
Quay

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK
TEMPORARILY ABANDON
PULL OR ALTER CASING
OTHER

PLUG AND ABANDON
CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIAL WORK
COMMENCE DRILLING OPNS.
CASING TEST AND CEMENT JOBS
OTHER Intermediate Casing

ALTERING CASING
PLUG AND ABANDONMENT

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2730'. Ran 68 jts 8-5/8" 32# J-55 ST&C casing set 2730'. 1-Texas Pattern guide shoe set 2730'. Halliburton float collar set 2688'. Cemented w/675 sacks Pacesetter Lite w/5# Hiseal, 1/4# cellseal, 3% CaCl2. Tailed in w/200 sacks Class "C" w/2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 4:30 AM 11-5-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 20 sacks. Drilled out 12:00 AM 11-6-84. WOC 19 hrs and 30 minutes. Cut off and welded on flow nipple. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED BY [Signature] TITLE Production Supervisor DATE 11-7-84

APPROVED BY [Signature] TITLE DISPATCH DATE 11-13-84

CONDITIONS OF APPROVAL, IF ANY: