

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- P&A	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name T-4 Filly's Tooth
3. Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER L, 2265.9 FEET FROM THE South LINE AND 756.2 FEET FROM THE West LINE, SECTION 12 TOWNSHIP 10N RANGE 27E NMPM.	10. Field and Pool, or wildcat Undesignated
11. Elevation (Show whether DF, RT, GR, etc.) 4295.7' GR	12. County Quay

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 7705'

Propose to plug and abandon well as follows:

1. Spot cement plug on existing retainer @7240' with top of plug up to 7040' or higher.
This plug will cover open Penn perforations 7093-7197'. Tag this plug.

2. Cut and pull 5½" casing from approximately 5350'. Cement bond log shows cement top at 5415'.

3. Spot 100' cement plug 50' in and out of 5½" casing stub.

4. Spot 100' cement plug from 3400-3500' across top of Abo/Sangre De Christo @3442'.

5. Spot 100' cement plug from 2680-2780' across 8-5/8" intermediate casing shoe at 2730'.

6. Put 15 sack cement plug at surface with regulation abandonment marker.

Note: All plugs except surface plug will consist of at least 35 sacks of cement.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature]

TITLE Production Supervisor

DATE 6-26-85

APPROVED BY _____

TITLE FOR

DATE 7-2-85

CONDITIONS OF APPROVAL, IF ANY: