

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER-	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name T-4 Filly's Tooth
3. Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> , <u>2265.9</u> FEET FROM THE <u>South</u> LINE AND <u>756.2</u> FEET FROM THE <u>West</u> LINE, SECTION <u>12</u> TOWNSHIP <u>10N</u> RANGE <u>27E</u> NMPM.	10. Field and Pool, or Wildcat Undes. Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4295.7' GR	12. County Quay

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☒ Production Casing, Perforate, Treat

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

TD 7705'. Ran 184 joints of 5-1/2" 15.5 and 17# casing as follows: 15 jts of 5-1/2" 17# J-55 LT&C; 12 jts of 5-1/2" 15.5# J-55 LT&C and 157 jts of 5-1/2" 15.5# J-55 LT&C (total 7711') of casing set 7705'. Float shoe set at 7705'. Float collar set at 7680'. Cemented w/950 sx C1 C .5% CF-1, .2% AFS and 3% KCL. Mixed at 14.8 ppg, yield of 1.32 cubic feet/sack = 1254 cubic feet slurry = 223 bbls. Displaced w/182.7 bbls fresh water. PD 5:00 PM 12-4-84. Did not bump plug. WOC 18 hours. WIH and perforated 7265-71' w/4 SPF. Very weak blow. Recovered no gas or oil after swab run. Acidized perforations 7265-71' w/1000 gals 5% acid with Claymaster and 30 ball sealers plus N₂. Swabbing and testing well.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Production Supervisor DATE 12-20-84

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 12-20-84

CONDITIONS OF APPROVAL, IF ANY: