

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-053-20015

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Twining Drilling Corporation

3. Address of Operator

332 White Oak Drive NE, Albuquerque, NM 87122-1411

7. Lease Name or Unit Agreement Name:

NFT

8. Well No.

3

9. Pool name or Wildcat

Wildcat

4. Well Location

Unit Letter B : 665 feet from the NORTH line and 1975 feet from the EAST line

Section 27

Township 4N

Range 1E

NMPM

County

Socorro

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

5,300' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

On 4-4-02 Eunice Well Services, Inc. laid down all 5½" pipe in hole. At 11:00 American Energy Services, Inc. rolled hole w/92 BBL H2O, circulated clean with no apparent salt problems. At 11:25 pump 25 sks cement @ 15.6 ppg, displaced w/23 BBL H2O, Plug #1 (4400'-4084'); At 13:00 set bridge plug @ 1250' bumped, held with no problems; At 13:30 pump 35 sks @ 15.6 ppg, displaced w/6 BBL H2O, Plug #2 (1220'-1250'); At 14:00 pump 10 sks @ 15.6 ppg displaced w/1 BBL H2O, Surface plug (120' to surface). On 4-5-02 at 10:00 BOP and Braden cut loose, dry hole marker welded in place by Bill Shupe certified welder. Cellar will be removed and site remediated as soon as reserve pits are dry.

Inspected
4/12/02 OK
REL

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronald Lewis Rutherford TITLE Vice-President DATE 04/8/02

Type or print name RONALD LEWIS RUTHERFORD

Telephone No. 505-856-2238

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 4/12/02

Conditions of approval, if any: