



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office New Mexico  
Lease No. 05140  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 28

19<sup>54</sup>

Lockhart

Well No. 2 is located 660 ft. from NEX line and 660 ft. from EX line of sec. 33

NW<sup>1</sup>/<sub>4</sub> NW<sup>1</sup>/<sub>4</sub>  
(1/4 Sec. and Sec. No.)

4S. 6E.  
(Twp.) (Range)

N.M.P.M.  
(Meridian)

Wildcat  
(Field)

Socorro  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 5691 ft. ground level

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Will set 300 feet of 10" casing, or more, and cement from top to bottom, using Halliburton Cementing Co. Will drill well with rotary rig to a depth of 4,000 feet or granite or production, starting soon.

COPY

COPY

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company J. R. Lockhart,

Address Box 101

Truth or Consequences, N.M.

By /S/ J. R. Lockhart

Title Owner