

GEORGE HOLTAMER

in Office

edit	54
colla	55
colla	56
edit	57
colla	58
edit	59
colla	60
edit	61
colla	62
edit	63
colla	64
edit	65
colla	66
edit	67
colla	68
edit	69
colla	70
edit	71
colla	72
edit	73
colla	74
edit	75
colla	76
edit	77
colla	78
edit	79
colla	80
edit	81
colla	82
edit	83
colla	84
edit	85
colla	86
edit	87
colla	88
edit	89
colla	90
edit	91
colla	92
edit	93
colla	94
edit	95
colla	96
edit	97
colla	98
edit	99
colla	100

RECEIVED
JAN 23 1946
RECEIVED

CIA 060

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). **SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.**

212 San Francisco St., El Paso, Texas

Address

Well No.

1

SE-1 SE-1

25

1800

Well is 4620 feet south of the North line and 660 feet west of the East line of Section 27

If State land the oil and gas lease is No. _____ Assignment No. _____

If patented land the owner is Michael Malda Address Corona, New Mexico

If Government land the permittee is _____ Address _____

The Lessee is Dale Resler Address El Paso, Texas

Drilling commenced July 23, 1945 Drilling was completed January 7, 1946

Name of drilling contractor S. P. Yates Address 311 Carper Bldg., Artesia, N. M.

Elevation above sea level at top of casing _____ feet.

The information given is to be kept confidential until _____

No. 1, from None to _____

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

No. 5, from _____ to _____

No. 6, from _____ to _____

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	585	to	600	feet.	35
No. 2, from	922	to	940	feet.	18
No. 3, from	1703	to	1725	feet.	22
No. 4, from	3325	to	3335	feet.	10

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15 1/2"	13"	665'	Mudded			
12 1/2"	10 3/4"	1675'	50 Sacks	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
 Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
 Cable tools were used from 0 feet to 3350 feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing Dry Hole, 19____
 The production of the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
 If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
 Rock pressure, lbs. per sq. in. _____

EMPLOYEES

C. V. Miller

Driller

J. O. Miller

Driller

E. B. Fulton

Driller

T. D. Bradshaw

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 18th

day of January 1946

Delma F. Matthews
 Notary Public

My Commission expires Feb. 25, 1947

Artesia, New Mexico

Place

Jan. 18, 1946

Date

Name

Position

Drilling Contractor

Representing

Dale Resler

Company or Operator

Address 212 San Francisco St., El Paso, Texas

FORMATION RECORD

2

FROM	TO	THICKNESS IN FEET	FORMATION
0	45	45	Lime
45	65	20	Caliche, Pink
65	115	50	Caliche, Red Rock
115	175	60	White Sand and Gravel
175	225	50	Coarse Sand
225	260	35	Lime
260	410	150	Sand
410	415	5	Anhy.
415	620	205	Sand
620	635	15	Anhy.
635	650	15	Blue Shale
650	665	15	Brown Sandy Lime
665	695	30	Anhy., Brown
695	700	5	Red Shale
700	720	20	Red Bed
720	730	10	Lime, Brown
730	735	5	Sand
735	750	15	Anhy.
750	785	35	Sand
785	805	20	Conglomerate
805	830	25	Sand
830	860	30	Conglomerate
860	890	30	Anhy.
890	895	5	Anhy. & Red Bed
895	915	20	Red Shale
915	940	25	Lime
940	1000	60	Red Sandy Shale
1000	1065	65	Anhy, Brown
1065	1070	5	Red Shale
1070	1075	5	Anhy.
1075	1090	15	Red Shale
1090	1110	20	Anhy.
1110	1130	20	Red Shale
1130	1150	20	Anhy.
1150	1170	20	Red Shale
1170	1195	25	Red Bed
1195	1270	75	Red Shale
1270	1320	50	Red Shale & anhy.
1320	1415	95	Red Shale
1415	1420	5	Conglomerate
1420	1485	65	Red Shale
1485	1525	40	Anhy.
1525	1540	15	Red Shale
1540	1555	15	Anhy. & Red Shale
1555	1570	15	Anhy.
1570	1600	30	Red Shale
1600	1622	22	Sand, Red
1622	1640	18	Sandy Shale, Red
1640	1665	25	Red Sand
1665	1670	5	Lime
1670	1703	33	Blue Shale
1703	1725	22	Sand
1725	1740	15	Lime
1740	1755	15	Blue Shale
1755	1770	15	Lime
1770	1780	10	Blue Shale

