

MULTIPOINT AND ONE POINT BACK PRESSURE TEST FOR GAS WELL

Form C-122
Revised 9-1-65

Type Test: ☒ Initial ☐ Annual ☐ Special		Test Date: 7-4-87	
Company: Amoco Production Company		Connection:	
Pool: Bravo Dome		Formation: Tubb	
Completion Date: 8-19-74		Total Depth: 2670	Plug Back TD: 2417
		Elevation: 4750	Unit: BDCDGU
Csg. Size: 4.50	Wt. 9.5	d 4.1	Set At 2670
Perforations: From 2186 To 2404		Well No. 2034-3610	
Csg. Size: 2.375	Wt. 4.6	d 1.995	Set At 2176
Perforations: From To		Unit Sec. Twp. Rge. 0 36 20 34	
Type well - Single - Rinddenhead - G.G. or G.O. Multiple Single		Packer Set At 2146	County: Union
Producing Thru Tubing	Reservoir Temp. °F 90	Mean Annual Temp. °F 50	Baro. Press. - P _a 12.25
State: New Mexico			
L	H	G _g	% CO ₂ 100
			% N ₂ 0
			% H ₂ S 0
Prover		Meter Run 4.0	Taps Flange

FLOW DATA						TUBING DATA		CASING DATA		Duration of Flow	
NO.	Prover Line Size	X	Orifice Size	Press. p.s.i.g.	Diff. h _w	Temp. °F	Press. p.s.i.g.	Temp. °F	Press. p.s.i.g.		Temp. °F
SI							315		0		24 hrs
1.	4.026 x	1.875		194	41	58	192	58	0		24 hrs
2.	4.026 x	1.875		207	33	58	204	58	0		24 hrs
3.	4.026 x	1.875		223	24	61	220	61	0		24 hrs
4.	4.026 x	1.875		234	19	59	230	59	0		24 hrs
5.											

RATE OF FLOW CALCULATIONS							
NO.	Coefficient (24 Hour)	$\sqrt{h_w P_m}$	Pressure P _m	Flow Temp. Factor F _L	Gravity Factor F _g	Super Compress. Factor, F _{pv}	Rate of Flow Q, Mcfd
1.							1354
2.							1273
3.							1151
4.							1018
5.							

NO.	P _t	Temp. °R	T _g	Z	Gas Liquid Hydrocarbon Ratio	Mcf/bbl.
1.					0	
2.						
3.						
4.						
5.						

NO.	P _t	P _w	P _w ²	P _t ² - P _w ²	(1) $\frac{P_t^2}{P_t^2 - P_w^2} =$	(2) $\left[\frac{P_t^2}{P_t^2 - P_w^2} \right]^n =$
1.	204.25	41,718	65,374		1.6381	1.4608
2.	216.25	46,764	60,328			
3.	232.25	53,940	53,152			
4.	242.25	58,685	48,407			
5.						

Absolute Open Flow		1978	Mcf @ 15.025	Angle of Slope @	37.5219	Slope, n	0.7679
--------------------	--	------	--------------	------------------	---------	----------	--------

Remarks: Test was run from a low flowing tubing pressure to a high flowing tubing pressure to minimize liquid loading effects.

Approved by Commission:	Conducted By: RANDY MAHANNAH	Calculated By: RICHARD ROETH	Checked By:
-------------------------	---------------------------------	---------------------------------	-------------