

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Carbon dioxide well

2. Name of Operator

Amerada Hess Corporation

3. Address of Operator

Drawer D, Monument, New Mexico 88265

4. Location of Well

UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM

THE West LINE, SECTION 9 TOWNSHIP 30-N RANGE 31-E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name

Burner

9. Well No.

1

10. Field and Pool, or WHOLE

Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)

6052' GR

12. County

Union

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☐

OTHER Progress ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

8-25-80 to 9-15-80 - Schlumberger ran junk basket & gauge ring in 7" csg. fr. surface to 1861'. Ran GR, bond log & collar locator. Found good cement fr. 989' to 1861'. Ran 2-3/8" tbq. set at 1629'. Tested 7" csg. to 2000#. Held OK. Circ. hole w/2% KCl water & spotted 4 bbls. 7 1/2% acid fr. 1623' to 1565'. Schlumberger perf. 7" csg. opposite Glorieta zone fr. 1560' to 1618' w/total of ten shots. Ran tbq. set at 1538'. Swabbed 24 bbls. KCl water. Nowsco blew csg. dry w/nitrogen. Dowell acidized Glorieta zone thru 7" csg. perf. fr. 1560' to 1618' w/total of 14000 gal. foam acid & displaced w/nitrogen. Flowed back 30 bbls. water. Swabbed. Dowell fraced Glorieta zone thru 7" csg. perf. fr. 1560' to 1618' w/20,000 gal. 50/50 YF CO2 liquid CO2 & 40,000# sand in stages. Swabbed.

Presently closed in for further evaluation.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. B. Fisher

TITLE Supv. Adm. Ser.

DATE 9-16-80

APPROVED BY Carl Libbey

TITLE SECTION CHIEF

DATE 9-22-80

CONDITIONS OF APPROVAL, IF ANY: