

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED
SEP 15 1980

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		<input checked="" type="checkbox"/>
U.S.O.S.		
LAND OFFICE		
OPERATOR		

OIL CONSERVATION DIVISION
SANTA FE

Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER- CO² Gas Well

2. Name of Operator
Amerada Hess Corporation

3. Address of Operator
Drawer D, Monument, New Mexico 88265

4. Location of Well
UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE East LINE, SECTION 4 TOWNSHIP 29N RANGE 31E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name
Wilkinson

9. Well No.
1

10. Field and Pool, or Wildcat
Wildcat

11. Elevation (Show whether DF, RT, GR, etc.)
6049' GR

12. County
Union

10. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>Progress</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drld. conductor hole to 35' & set 13-3/8" conductor pipe & cemented w/5 yards Ready Mix. Spudded 12-1/4" hole @ 4 PM 7-1-80. Drld. 12-1/4" hole to 376' & set 9-5/8" 36# csg. at 367' & cemented w/300 sks. Class "H" cement mixed w/3% CaCl. Circ. out 10 sks. cement, WOC & drld plug, cement & shoe & tested w/1000#. Held OK. Drld. 8-3/4" hole fr. 376' to 3450' w/air. Hole sluffing off. Mixed mud and conditioned hole. Drld. fr. 3450' to 3960' drld. w/mud. Attempted to log. No results. Wash, ream & condition hole. Ran 7" 20# csg. set @ 1138' & cemented w/400 sks. cement w/additives. WOC & drld. cement & shoe. Washed & reamed & circ. to condition hole @ 1160'. Set cement retainer in 7" csg. @ 1100' & pumped 100 sks. Class "H" cement mixed 2% CaCl. Pulled out of retainer & reversed out 1/2 bbl. cement. Cut off csg., installed tbg. head & released drlg. rig. @ 12 Noon 7-22-80

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED EA Fisher TITLE Supv. Adm. Ser. DATE 8/21/80

APPROVED BY Carl M. Wray TITLE _____ DATE 9/22/80

CONDITIONS OF APPROVAL, IF ANY: