

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
--

7. Unit Agreement Name
--

8. Form or Lease Name
H. R. Brown NCT-1

9. Well No.
1

10. Field and Pool, or Wildcat
Undesignated

12. County
Union

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPER OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER- Carbon Dioxide

Name of Operator
Texaco, Inc.

Address of Operator
P. O. Box 728, Hobbs, New Mexico 88240

1. Location of Well
UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE West LINE, SECTION 29 TOWNSHIP 30N RANGE 30E

15. Elevation (Show whether DF, RT, GR, etc.)
6410' (GR)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Perforate, Treat & P & A Well <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TOTAL DEPTH 2998'
 PLUG BACK TOTAL DEPTH 1753'
 9 5/8" OD 32.3# H-40 Csg Set @ 821'
 7" OD 20# K-55 Csg Set @ 1402'
 4 1/2" OD 10.5# K-55 Csg Screwed Into Drill Pipe @ 1758'

- Perforate 4 1/2" Csg. w/2-BPF from 1480'-1494', 1532'-1540', 1556'-1564', 1608'-1616', 1654'-1666', 1684'-1694' & 1735'-1749'.
- Acidize perms. 1480'-1749'-w/6000 gals. 7 1/2% MSR-100 60 Quality Nz Foamed acid & 144 Ball Sealers.
- Set CIBP @ 1330' & Spot 40' (4Sx) Cement on plug. PBID 1290'.
- Perforate 4 1/2" Csg. w/2 Bullets PF from 940'-960', 1016'-1024', 1076'-1086', 1103'-1120', 1127'-1140', 1160'-1168', 1177'-1180', 1183'-1192', & 1202'-1212'.
- Acidize perms. 940'-1212' w/7000 gals. 7 1/2% MSR-100 60 Quality Foamed Acid w/120 Ball Sealers. Flush w/Nitrogen.
- Set CIBP @ 850' & Dump 40' Cement on plug to 810'.
- Set 5 Sx. Cement plug from 50'-Surface.
- Set Dry Hole Marker & Clean Up. Well P & A, 12/6/80.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Asst. Dist. Supt. DATE 12/10/80

APPROVED BY [Signature] TITLE SENIOR PETROLEUM GEOLOGIST DATE 3/23/81

CONDITIONS OF APPROVAL, IF ANY: