

N. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		✓
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT "M" FORM C-101 FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☐ Fee ☒
6. State Oil & Gas Lease No.		7. Unit Agreement Name
8. Farm or Lease Name Amoco Production Company		9. Well No. Hutcherson B
10. Field and Pool, or Wildcat P. O. Box 68 Hobbs, NM 88240		11. County Und. Tubb
12. Location of Well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1974 FEET FROM THE East LINE, SECTION 21 TOWNSHIP 19-N RANGE 34-E		13. Elevation (Show whether DF, RT, GR, etc.) 4828' GL
14. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ FULL OR ALTER CASING ☐ OTHER P X A ☒		SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ ALTERING CASING ☐ COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐ CASING TEST AND CEMENT JOB ☒ OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 11-12-80 Stinebaugh Drilling (Rig #4) spudded a 12-1/4" hole at 1:00 p.m. Drilled to a TD of 701' and ran 8-5/8" casing set at 700'. Cemented with 450 SX Class H cement. Plugged down at 12:30 p.m. 11-15-80. Circulated 100 SX. WOC 38 hrs. Tested casing with 800# for 1 hr. Test OK. Reduced hole to 7-7/8" and resumed drilling. Drilled to a TD of 1740' and lost circulation. Moved out Stinebaugh Rig 12-1-80. Moved in Layton Exploration (Rig #1) 12-12-80. Attempted to run to TD. Unable to do so. Twisted off drill pipe. Recovered fish. Lost circulation. Unable to return to TD. Propose to P X A per the following procedure:

Spot 100 SX Class H cement plug 1411'-900'. WOC 4 hrs. and tag plug. Spot 80 SX Class H cement plug 800'-600'. Spot 20 SX surface plug.

0+2-NMOCD, SF 1-Hou 1-Susp 1-BD

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Admin. Analyst DATE 1-22-81

APPROVED BY Carl Ulvog TITLE SENIOR PETROLEUM GEOLOGIST DATE 1-23-81
CONDITIONS OF APPROVAL, IF ANY