

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.

30-059-20069

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER CO2

2. Name of Operator

Amoco Production Company

3. Address of Operator

PO Box 606, Clayton, NM 88415

4. Well Location

Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East Line

Section 27 Township 20N Range 34E NMPM Union County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4750' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: Install casing Liner ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRUSU

RUN & SET 1.625" BLANKING PLG IN PROFILE

BLEED TBG TO 0 PSI

NUBOP

RELEASE ON/OFF TOOL

SWAB CSG DOWN, REC AS MUCH FLUID AS POSSIBLE

LAYDOWN FG TBG

RUN POLYBORE GAUGE RING

OPTION #1

IF GAUGE RING GOES & LOOKS OK WHEN PULLED:
RUN 10-3 1/8" DRILL COLLARS (COLLARS EQUIPPED
WITH 2 7/8" FAC BOX ON TOP). RIG UP ROLLER
REDUCTION

UNIT; RUN POLY LINER TO TOP OF PKR; FISH DRILL
COLLARS FROM POLYLINER W/TBG FUSE ON
WELLHEAD FLANGE; INSTALL SS B-1 ADAPTER &
MASTER VALVE; INSTALL METER RUN; RU
LUBRICATOR & FISH BLANKING PLUG; RETURN
WELL TO PRODUCTION; RDMOSU

OPTION #2

IF GAUGE RING DOES NOT MAKE IT TO PKR DEPTH
OR COMES OUT WITH SIGNS OF CSG DAMAGE,
RERUN 3 1/2" FG PRODUCTION TBG; LATCH ON TO
PKR; FISH BLANKING PLUG; PRESS TEST CSG & PKR
TO 500 PSI; RETURN WELL TO PRODUCTION;
RDMOSU

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Billy E. Prichard

TITLE

Field Foreman

DATE

2/27/97

TYPE OR PRINT NAME

Billy E Prichard

TELEPHONE NO.

374-3053

(This space for State Use)

APPROVED BY

Billy E. Prichard

TITLE

DISTRICT SUPERVISOR

DATE

3/17/97

CONDITIONS OF APPROVAL, IF ANY: