

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-059-20094
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☐ GAS WELL ☐ OTHER C02	7. Lease Name or Unit Agreement Name B0C0G0U-1935
2. Name of Operator Amoco Production Company	8. Well No. 041
3. Address of Operator PO Box 606, Clayton, NM 88415	9. Pool name or Wildcat Tubb
4. Well Location Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East Line Section 4 Township 19N Range 35E NMPM Union County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4635' GR	

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: Install Casing Liner ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work; SEE RULE 1103.

MIRUSU
RUN & SET 1.625" BLANKING PLG IN PROFILE
BLEED TBG TO 0 PSI
NUBOP
RELEASE ON/OFF TOOL
SWAB CSG DOWN, REC AS MUCH FLUID AS POSSIBLE
LAYDOWN FG TBG
RUN POLYBORE GAUGE RING
OPTION #1
IF GAUGE RING GOES & LOOKS OK WHEN PULLED:
RUN 10-3 1/8" DRILL COLLARS (COLLARS EQUIPPED
WITH 2 7/8" PAC BOX ON TOP); RIG UP ROLLER
REDUCTION

UNIT; RUN POLY LINER TO TOP OF PKR; FISH DRILL
COLLARS FROM POLYLINER W/TBG FUSE ON
WELLHEAD FLANGE; INSTALL SS B-1 ADAPTER &
MASTER VALVE; INSTALL METER RUN; RU
LUBRICATOR & FISH BLANKING PLUG; RETURN
WELL TO PRODUCTION; RDMOSU
OPTION #2
IF GAUGE RING DOES NOT MAKE IT TO PKR DEPTH
OR COMES OUT WITH SIGNS OF CSG DAMAGE,
RERUN 3 1/2" FG PRODUCTION TBG; LATCH ON TO
PKR; FISH BLANKING PLUG; PRESS TEST CSG & PKR
TO 500 PSI; RETURN WELL TO PRODUCTION;
RDMOSU

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Billy E. Prichard TITLE Field Foreman DATE 2/27/97
TYPE OR PRINT NAME Billy E Prichard TELEPHONE NO. 374-3053

(This space for State Use)

APPROVED BY Ry Ephraim TITLE DISTRICT SUPERVISOR DATE 3/17/97
CONDITIONS OF APPROVAL, IF ANY: