

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	11
LAND OFFICE	1
OPERATOR	1

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-101
Revised 10-1-78

5A. Indicate Type of Lease
STATE ☐ FEDERAL ☒
5. State Oil & Gas Lease No.

API # 30-059-20277

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of work		b. Type of Well DRILL ☒ DEEPEN ☐ PLUG BACK ☐ OIL WELL ☐ GAS WELL ☒ CO2 ☐ OTHER ☐		19. Proposed Depth 2900'		19A. Formation Tubb		20. Rotary or C.L.	
2. Name of Operator Amoco Production Company				9. Well No. 2134 321 G		Bravo Dome Carbon Dioxide Gas Unit			
3. Address of Operator P.O. Box 68 Hobbs, New Mexico 88240				17. County Lincoln		Bravo Dome Carbon Dioxide Gas Unit 640-Acre Area			
4. Location of well UNIT LETTER <u>9</u> LOCATED <u>1650</u> FEET FROM THE <u>North</u> LINE <u>1650</u> FEET FROM THE <u>East</u> LINE OF SEC. <u>32</u> TWP. <u>21-N</u> R. <u>34-E</u>				21A. Kind & Status Plug. bond Blanket-on-file		21B. Drilling Contractor N/A		22. Approx. Date work will start	
18. Elevation (show whether DT, H, etc.) 4909' GL				23.					

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
12-1/4"	9-5/8"	32.30#	700'	Circulate	surface
8-3/4"	7"	20.0#	2900'	Tieback to 9-5/8" surface	

Propose to drill and equip well in the Tubb formation. After reaching TD logs will be run and evaluated. Perforate and stimulate as necessary in attempting commercial production.

Mud Program: 0 - 700' Native Spud Mud
700 - TD KCL Salt Water Gel-Starch

APPROVAL VALID FOR 180 DAYS
PERMIT EXPIRES 3-18-86
UNLESS DRILLING UNDERWAY

BOP Diagram attached.

O+5-HMOCD,SF 1-J. R. Barnettt, HOU Rm. 21.156 1-F. J. Nash, HOU Rm. 4.206 1-WF, C 1-WF,
1-Susp, 1-CMH 1-Amerada 1-Amerigas 1-Cities Service 1-Conoco 1-CO2 in Action 1-Sun
1-Excelsior 1-Tex 1-Exxon

4. ABOVE SPACE DESCRIBE PROPOSED PROGRAM. IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRO-
DUCIVE ZONE. GIVE SHUT-IN PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Charles M. Larring Title Administrative Analyst (SG) Date 9-16-85

(This space for Signer Use)

APPROVED BY Boz E. Johnson TITLE DISTRICT SUPERVISOR DATE 9-18-85

CONDITIONS OF APPROVAL, IF ANY:

NEW MEXICO OIL CONSERVATION COMMISSION
WELL LOCATION AND ACREAGE DEDICATION PLAT

Form O-110
Supersedes O-128
Effective 1-1-85

All distances must be from the outer boundaries of the Section

Owner AMOCO PRODUCTION COMPANY			Lease Bravo Dome Carbon Dioxide Gas Unit		Well No. 2134 321G
Section Letter G	Section 32	Township T21N	Range R34E	County UNION	
Well Location of Well: 1650 feet from the NORTH line and 1650 feet from the EAST line					
Ground Level Elev. 4909	Producing Formation Tubb	Pool Bravo Dome 640 Acre Area		Dedicated Acreage: 640 Acres	

1. Outline the acreage dedicated to the subject well by colored pencil or hatchure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☒ Yes ☐ No If answer is "yes," type of consolidation Agreement or Forced Pooling

If answer is "No," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.)

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.

UNLEASED	5201 PT Amoco Prod. Co. State of New Mexico-all		CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.	
			Name: <i>Charles M. Loring</i> Position: <i>Admin. Analyst (SG)</i> Company: <i>Amoco Production Co.</i> Date: <i>9-16-85</i>	
85 PT Amoco Production Company J. C. Heimann et al			I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.	
			N.M.L.S. NO. 5103	

0 500 1000 1500 2000 2500 3000 3500 4000 4500 5000 5500 6000 6500 7000 7500 8000 8500 9000 9500 10000

STANDARD 2000 PSI W.P. BOP STACK

1. Blow-out preventers may be manually operated.
2. All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
3. Bell nipple above blow-out preventer shall be same size as casing being drilled through.
4. Kelly cock to be installed on kelly.
5. Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
6. Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
7. Double or space saver type preventers may be used in lieu of two single preventers.
8. BOP rams to be installed as follows:

Top preventer	-	Drill pipe or casing rams
Bottom preventer	-	Blind rams

*Amoco District Superintendent may reverse location of rams.
9. Extensions and hand wheels to be installed and braced at all times.
10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

