

UNITED STATES
DEPARTMENT OF THE INTERIOR
BIOLOGICAL SERVICE

Lead Office: _____

Lead No: _____

City: _____

IS ALSO REPORTS ON WELLS

[illegible]

50

$\frac{\partial}{\partial t} \left(\rho \frac{\partial u}{\partial x} \right) = - \frac{\partial}{\partial x} \left(\rho \frac{\partial^2 u}{\partial x^2} \right)$

Figure 6

10

Figure 1. Schematic representation of the experimental design. The subjects were divided into two groups: the control group and the experimental group. The control group was divided into two subgroups: the control group and the experimental group. The experimental group was divided into two subgroups: the control group and the experimental group.

$\frac{1}{2} \left(\frac{1}{2} \right) = \frac{1}{4}$

Index

Ref. 10

66-111-10000

ILLEGIBLE

1. *Staphylococcus aureus*

Company 21

Address


...and the

Keywords: child sexual abuse; disclosure; social support; self-esteem

11

B. B. Gilman

... ..



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____
Lease No. _____
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA)

November 30, 1952

Well No. 1 Federal is located 2,950 ft. from $\left\{ \begin{smallmatrix} N \\ S \end{smallmatrix} \right\}$ line and 2,974 ft. from $\left\{ \begin{smallmatrix} E \\ W \end{smallmatrix} \right\}$ line of sec. 29

NE 29 (4 sec. and 4 sec. No.) 26N (Town) 33E (Range) (Meridian)
Wildcat (Well) Union (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 5,474 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Will run cement plug from 2,610' to 2,660' - Top Granite Wash. Will run cement plug from 240' to 290' - Bottom of Surface Casing. Will cement cellar with marker

Verbal approval by Mr. Trawick

ILLEGIBLE

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Drilled for Western Oil and Gas Company by North American Drilling Co.

Address Box 469

Cushing, Oklahoma

By D. B. Gilman

Title Vice President

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____

Lease No. YM021009

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

ILLEGIBLE

October 16, 1952

Well No. 1 is located 2,950' ft. from N line and 2,974' ft. from W line of sec. 291/4 - Sec. 29

(1/4 Sec. and Sec. No.)

26N

(Twp.)

33E

(Range)

(Meridian)

Union County

(Field)

Union County,

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is unknown ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. Formations to Be Encountered: Dakota SS. Surface
Blaine Anhy. 2,000'
Granite Wash: 2,500'
Miss. Lime 4,300'
Arbuckle Lime 4,500'
2. 250' - 8-5/8" Surface Cag., H-40, Rng-2; Sals. - Cement to be Circulated.
3-1/2" Oilstring; J-35; Rng-2; Sals. - Sufficient to test Oil or Gas Sands
Encountered - Same for Cement.
Water Base Mud Surface to Total Depth of Sufficient Nature to Drill and
Test Formations with Minimum amount of Damage to Formations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company WESTERN OIL & GAS COMPANYAddress P. O. Box 3925Oklahoma City 6, Oklahoma

By

Title

G.J. Forrester
Partner