

A 10x10 grid with a point labeled '0' at the intersection of the 5th column and 9th row, and a point labeled '3' at the intersection of the 4th column and 5th row.

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NEW MEXICO
MAIN OFFICE CCC

1954 OCT 20 PM 2:05 WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

Gruemmer Industries

(Company or Operator)

R. L. Black

(Lease)

Well No. 1 R.L. Blk in NW $\frac{1}{4}$ of NE $\frac{1}{4}$, of Sec. 3, T. 29N, R. 29E, NMPM.

Pool Union County

Well is 660 feet from N line and 1980 feet from E line.

of Section 3 If State Land the Oil and Gas Lease No. is -

Drilling Commenced July 8, 1954 Drilling was Completed September 11, 1954

Name of Drilling Contractor Baker & Keech

Address..... Borger, Texas

Elevation above sea level at Top of Tubing Head.....6687'..... The information given is to be kept confidential until

CO₂ Gas Sands

~~XXXXXXXXXXXXXXXXXXXX~~

No. 1, from 1182 to 1192 No. 4, from - to -

No. 2, from 2550 to 2605 No. 5, from - to -

No. 3, from 2005 to 2006 No. 6, from 2005 to 2006

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 285 to 290 feet. 3 Bailers / hour

No. 2, from 1660 to 1695 feet. 1 Bailer / hour

No. 3, from 1695 to 1710 feet. 2 Bailers / hour

No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8"	28#	Used	955	Texas		None	-
7"	17-24#	Used	2217	Texas			
5"	14#	Used	352	Texas			Liner

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8"	955	125	Displacement	Plug None	None
8"	7"	2217	360	" Plug	None	None
7"	5"	2205-2557	250	Squeeze	None	None

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perforations	1182-1192	50 Shots
--------------	-----------	----------

Perforations 2550-2557 58 Shots

Result of Production Stimulation 60 MCF/Day 2550-2605 Open Flow

290 MCF/Day 1182-1192

..Depth Cleaned Out.