

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator BRANA CORPORATION	8. Farm or Lease Name Penteco-Trinity
3. Address of Operator 1223 First Interstate Bldg, 320 Gold Ave. SW, Albuquerque, NM 87102	9. Well No. 2
4. Location of Well UNIT LETTER <u>G</u> <u>1670</u> FEET FROM THE <u>North</u> LINE AND <u>1960</u> FEET FROM THE <u>East</u> LINE, SECTION <u>19</u> TOWNSHIP <u>6N</u> RANGE <u>2W</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 5570 grnd	12. County Valencia

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER <u>Well history</u> <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 9 7/8" hole on 1-4-85. Drilled to 574' with native mud. Ran 6 joints 7", 23#, J casing & set at 223'. Cemented with 100 sxs Class A w/2% CaCl₂. Cement circulated to surface. POB @ 1:30PM, 1-8-85. Drilled 6 1/4" hole to 2840' with gel mud. Ran logs. Ran 4 1/2", 9.5#, J casing and set @ 899'. Cemented with 400 sxs Class A w/1/4#Flo/sx/ POB @ 8:26 PM 3-10-85. Cement circulated. RR, now WO Compl. Rig. From TD to bottom of cement plug filled with gel mud @ 9.0#/gal.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Morris B. Jones, Engineer DATE 3-15-85

APPROVED BY [Signature] TITLE Sr. Petroleum Engineer DATE 3-21-85

CONDITIONS OF APPROVAL, IF ANY: