Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103
<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources		Revised June 10, 2003 WELL API NO.
District II	OIL CONSERVATION DIVISION		30-015-32874
1301 W. Grand Ave., Artesia, NM 88210 District III	1220 South St. Francis Dr.		5. Indicate Type of Lease STATE X FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505		6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505			
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			State B
PROPOSALS.)		8. Well Number	
1. Type of Well: Oil Well x Gas Well Other RECEIVED		#5	
2. Name of Operator APR 1 5 2004		9. OGRID Number	
The Wiser Oil Company	OED-ARTESIA		022922
3. Address of Operator P. O. Box 2568 Hobbs, New Mexic			10. Pool name or Wildcat Greyburg Jackson
4. Well Location			
11 11 11 0		OUTH	1330' EAST
Unit Letter_O Section 16	:feet from the Township17S	Range 31E	feet from theline NMPM EDDY County
	11. Elevation (Show whether D		
12. Chall Associate Day As Indiana Natura of Nation Days and Other Date			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:			
		REMEDIAL WOR	
		COMMENCE DE	
TEMPORARILY ABANDON	CHANGE PLANS		AILLING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	MULTIPLE X COMPLETION	CASING TEST A	ND [
OTHER:		OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date			
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion			
or recompletion. INTENT: COMPLETE AS SAN ANDRES/GREYBURG PRODUCING OIL AND GAS.			
SPUD DATE: 3/7/04			
8 5/8" 24# CASING SET @ 410' CEMENT CIRCULATED 5 1/2" 15.5# CASING SET @ 3900'. TOP OF CEMENT @ 1540' BY CEMENT BOND LOG. HAVE VOID IN CEMENT FROM			
2300'-2800'. HAD WATERFLOW OF 1 BPM @ 2800'. DV TOOL @ 2705' AND ECP @ 2710'.			
<ul> <li>Perforate lower San Andres 3780-82,70-75,52-58,41-48,8-11,3694-97,31-33 with 2 spf.</li> </ul>			
Acidize with 3000 gals acid. Swab load back.			
<ul> <li>Perforate 3403-09,17-22,27-29. Acidize with 1500 gals acid. Swab load back.</li> <li>Perforate Greyburg @ 3044-48,83-85,99-3104,07-21,34-38,53-63,68-73,3228-33,37-45,55-66.</li> </ul>			
<ul> <li>Acidize with 2000 gals acid. Swab load back. Prepare to fracture treat Greyburg- Vacumme.</li> </ul>			
<ul> <li>Perforate casing @ 2790' and 2310'. Cement casing to fill void. Run CBL to determine cement void covered.</li> </ul>			
Place well on pump.			
1			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE ,	ones TITLE	Superin	tendent DATE 4/12/04
Type or print name	E-mail	address:	Telephone No.
(This space for State use)  APR 2 0 2004			
APPPROVED BY	TITLE	Westrict S	DATE
Conditions of approval if any			



3044· 3780′

1 85/8"@ 410' Cont Cir. 1540' 2300 DU Tool ] ECP 27/0' 5 2800' Cmt 5/2" 15,5 @ 3900'