District	Submit 3 Copies To Appropriate District Office <u>District I</u>	State of New Mexico Energy, Minerals and Natural Resources			Form C-103 Revised June 10, 2003 WELL API NO.		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS DOME FOR PROJOSAS 15 OR DIGHT OR THOSE BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROJOSALS.) 1. Type of Well: 2. Name of Operator Vates Petroleum Corporation 3. Address of Operator 105 S.4 "Street, Artesia, NM 88210 OGD-APTESIA 4. Well Location Unit Letter F : 2310 feet from the North line and 2310 feet from the West line Section 34 Township 21S Range 31E NMFM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3479 GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK PLUG AND ABANDON ABANDONMENT REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPPNS PLUG AND ABANDON ABANDONMENT 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion recompletion. 60904 - Reached TD 8300° at 1-45 PM. Set 5-1/2" 15.5# & 17# 1.55, LT&C casing at 8300°. Float collar set at 8255°. Cemented stage 1 with 250 ax Super "It" with additives, tailed in with 100 ax Class "C" with additives. Cement circulated. Cemented stage 2 with 275 ax Halliburton Lite "C" Premium Plus, tailed in with 100 ax Class "C" with additives. Cement circulated. Cemented stage 3 with 325 sx Halliburton Lite "C" Premium Plus, tailed in with 100 ax Class "C" with additives. Cement circulated. Tested easing to 1000 psi for 30 mins. 1 hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE: The production of the proposed of	1301 W. Grand Ave., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.			5. Indicate Ty	30-015-31929 pe of Lease X FEE Gas Lease No.	
2. Name of Operator Yates Petroleum Corporation JUN 1 8 7004 3. Address of Operator 105 S. 4* Street, Artesia, NM 88210 4. Well Location Unit Letter F : 2310 feet from the North line and 2310 feet from the West line Section 34 Township 21S Range 31E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3479 GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLAN DABANDON ALTERNIG ON ALTERNIG ON ALTERNIG CASING ALTERNICATION TO: PULL OR ALTER CASING MULTIPLE COMPLETION CHANGE PLANS 13. Describe proposed or completed operations. (Clearly state all pertined details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6/9/04 - Reached TD 8300' at 1:45 PM. Set 5:1/2" 15.5# & 17#1-55, LT&C casing at 8300'. Float collar set at 8255'. Cemented stage 1 with 250 sx Super "H" with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Cemented stage 2 with 275 sx Halliburton Lite "C" Premium Plus, tailed in with 100 sx Class "C" with additives. Cement circulated. Tested casing to 1000 psi for 30 mins. 1 hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE: TITLE: Regulatory Compliance Supervisor Tope for State use) POATE 1204 APPPROVED BY FOR RECORDS ONLY APPPROVED BY FOR RECORDS ONLY APPPROVED BY FOR RECORDS ONLY APPROVED BY FOR RECORDS ONLY APPROVED BY Trees at the state and complete to the best of my knowledge and belief. SIGNATURE: DATE 2 1 2004	(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:				Jacque AQJ State 8. Well Number		
Unit Letter F : 2310 feet from the North line and 2310 feet from the West line Section 34 Township 21S Range 31E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3479 'GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDON ALTERING CASING COMMENCE DRILLING OPNS PLUG AND ABANDON CEMENT JOB OTHER: COMPLETION CEMENT JOB OTHER: OTHER CASING SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion or recompletion. 6/9/04 - Reached TD 8300' at 1:45 PM. Set 5-1/2" 15.5# & 17# J-55, LT&C casing at 8300'. Float collar set at 8255'. Cemented stage 1 with 250 ax Super "H" with additives, tailed in with 50 ax Thixset. Cement circulated. Cemented stage 2 with 275 sx Halliburton Lite "C" Premium Plus with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Cemented stage 2 with 325 sx Halliburton Lite "C" Premium Plus, tailed in with 100 sx Class "C" with additives. Cement circulated. Tested casing to 1000 psi for 30 mins. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE: A stage of State use) APPPROVED BY FOR RECORDS ONLY APPPROVED BY FOR RECORDS ONLY APPPROVED BY FOR RECORDS ONLY In the stage of State use)	Yates Petroleum Corporation 3. Address of Operator	4 88210	JU	N 1 8 2004	10. Pool name	025575 e or Wildcat	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3479'GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE CASING TEST AND CEMENT JOB OTHER: OTHER: Production casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6/9/04 - Reached TD 8300' at 1:45 PM. Set 5-1/2" 15.5# & 17# J-55, LT&C casing at 8300'. Float collar set at 8255'. Cemented stage 1 with 250 sx Super "H" with additives, tailed in with 50 sx Thixset. Cement circulated. Cemented stage 3 with 325 sx Halliburton Lite "C" Premium Plus with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Cemented stage 3 with 325 sx Halliburton Lite "C" Premium Plus, tailed in with 100 sx Class "C" with additives. Cement circulated. Tested casing to 1000 psi for 30 mins. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE: TITLE: Regulatory Compliance Supervisor DATE: June 15, 2004 Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471 (This space for State use) APPPROVED BY FOR RECORDS ONLY APPPROVED BY FOR RECORDS ONLY	4. Well Location		North	line and 22			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND CEMENT JOB OTHER: Production casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6/9/04 - Reached TD 8300' at 1:45 PM. Set 5-1/2" 15.5# & 17# J-55, LT&C casing at 8300'. Float collar set at 8255'. Cemented stage 1 with 250 sx Super "H" with additives, tailed in with 50 sx Thisxet. Cement circulated. Cemented stage 2 with 275 sx Halliburton Lite "C" Premium Plus with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Cemented stage 3 with 325 sx Halliburton Lite "C" Premium Plus, tailed in with 100 sx Class "C" with additives. Cement circulated. Tested casing to 1000 psi for 30 mins. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE:	Section34	Township	21S Rai	nge31E	NMPMI	Eddy County	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING DEMPORABILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: OTHER: Production casing Table Completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6/9/04 - Reached TD 8300' at 1:45 PM. Set 5-1/2" 15.5# & 17# J-55, LT&C casing at 8300'. Float collar set at 8255'. Cemented stage 1 with 250 sx Super "H" with additives, tailed in with 50 sx Thixset. Cement circulated. Cemented stage 2 with 275 sx Halliburton Lite "C" Premium Plus with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Cemented stage 3 with 325 sx Halliburton Lite "C" Premium Plus, tailed in with 100 sx Class "C" with additives. Cement circulated. Tested casing to 1000 psi for 30 mins. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE: TITLE: Regulatory Compliance Supervisor DATE: June 15, 2004 Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471 (This space for State use) APPPROVED BY FOR RECORDS ONLY ITTLE DATE: June 15, 2004	12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data						
PULL OR ALTER CASING MULTIPLE CASING CEMENT JOB CEMENT JOB OTHER: OTHER: Production casing X 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6/9/04 - Reached TD 8300' at 1:45 PM. Set 5-1/2" 15.5# & 17# J-55, LT&C casing at 8300'. Float collar set at 8255'. Cemented stage 1 with 250 sx Super "H" with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Cemented stage 2 with 275 sx Halliburton Lite "C" Premium Plus with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Tested casing to 1000 psi for 30 mins. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE: TITLE: Regulatory Compliance Supervisor DATE: June 15, 2004 Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471 (This space for State use) APPPROVED BY FOR RECORDS ONLY TITLE: DATE OF TITLE			ON 🗌				
OTHER: Production casing I3. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6/9/04 - Reached TD 8300' at 1:45 PM. Set 5-1/2" 15.5# & 17# J-55, LT&C casing at 8300'. Float collar set at 8255'. Cemented stage 1 with 250 sx Super "H" with additives, tailed in with 50 sx Thixset. Cement circulated. Cemented stage 2 with 275 sx Halliburton Lite "C" Premium Plus with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Cemented stage 3 with 325 sx Halliburton Lite "C" Premium Plus, tailed in with 100 sx Class "C" with additives. Cement circulated. Tested casing to 1000 psi for 30 mins. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE: TITLE: Regulatory Compliance Supervisor DATE: June 15, 2004 Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471 (This space for State use) APPPROVED BY FOR RECORDS ONLY TITLE: DATE: June 15, 2004	_						
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6/9/04 - Reached TD 8300' at 1:45 PM. Set 5-1/2" 15.5# & 17# J-55, LT&C casing at 8300'. Float collar set at 8255'. Cemented stage 1 with 250 sx Super "H" with additives, tailed in with 50 sx Thixset. Cement circulated. Cemented stage 2 with 275 sx Halliburton Lite "C" Premium Plus with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Cemented stage 3 with 325 sx Halliburton Lite "C" Premium Plus, tailed in with 100 sx Class "C" with additives. Cement circulated. Tested casing to 1000 psi for 30 mins. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE: TITLE: Regulatory Compliance Supervisor DATE: June 15, 2004 Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471 This space for State use) APPPROVED BY FOR RECORDS ONLY TITLE: DATE: 12004	OTHER:	COMPLETION			ion casing	X	
1 with 250 sx Super "H" with additives, tailed in with 50 sx Thixset. Cement circulated. Cemented stage 2 with 275 sx Halliburton Lite "C" Premium Plus with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Cemented stage 3 with 325 sx Halliburton Lite "C" Premium Plus, tailed in with 100 sx Class "C" with additives. Cement circulated. Tested casing to 1000 psi for 30 mins. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE: TITLE: Regulatory Compliance Supervisor DATE: June 15, 2004 Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471 (This space for State use) APPPROVED BY FOR RECORDS ONLY TITLE: DATE: D	of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion						
SIGNATURE:	6/9/04 – Reached TD 8300' at 1:45 PM. Set 5-1/2" 15.5# & 17# J-55, LT&C casing at 8300'. Float collar set at 8255'. Cemented stage 1 with 250 sx Super "H" with additives, tailed in with 50 sx Thixset. Cement circulated. Cemented stage 2 with 275 sx Halliburton Lite "C" Premium Plus with additives, tailed in with 100 sx Class "C" Neat. Cement circulated. Cemented stage 3 with 325 sx Halliburton Lite "C" Premium Plus, tailed in with 100 sx Class "C" with additives. Cement circulated. Tested casing to 1000 psi for 30 mins.						
SIGNATURE:	I haraby cartify that the information	shove is true and comme	alata ta tha h	oot of my knowledge	and haliaf		
(This space for State use) APPPROVED BY FOR RECORDS ONLY DATE DATE 1 2004	SIGNATURE:	Huerta		-		DATE: <u>June 15, 2004</u>	
APPPROVED BYFOR RECORDS ONLY DATE DATE 1 2004			E-mail a	ddress: tinah@ypci	ım.com	Telephone No. 505-748-1471	
Conditions of approval if any:	, `	FOR RECORDS	ONLY TITLE			DATE 2 1 2004	