

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.  
30-015-32469

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Purple Gosling BBD State

8. Well No.

1

9. Pool name or Wildcat  
Chester

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4<sup>th</sup> Street Artesia, NM 88210

4. Well Location

Unit Letter M : 710 feet from the South line and 1040 feet from the West line

Section 2 Township 16S Range 28E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3568' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud and set surface casing ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

2/1/03 - Drilled 26" hole. Set 40' of 20" conductor. Redi-mix to surface. Notified Phil Hawkins with Artesia OCD of operations.

2/5/03 - Ran 10 joints 13-3/8" 48# H-40 8R STC casing set at 430'. Cemented with 245 sx Premium Plus with additives. Tailed in with 200 sx Premium Plus with additives. Circulated cement to surface. WOC 31 hrs. Reduced hole to 12-1/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE February 11, 2003

Type or print name Tina Huerta

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT IV SUPERVISOR

APPROVED BY [Signature] TITLE \_\_\_\_\_

DATE FEB 18 2003

Conditions of approval, if any: