

Submit 3 Copies To Appropriate District
Office,
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-29245

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
NSL-R-10621

7. Lease Name or Unit Agreement
Name:

State B Comm

8. Well No.
#4

9. Pool name or Wildcat
North Dagger Draw / Upper Penn

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

RECEIVED

2. Name of Operator
Mewbourne Oil Company 14744

OCT 12 2004

3. Address of Operator
PO Box 5270 Hobbs, NM 88241

OCC-ARTESIA

4. Well Location

Unit Letter E : 1650 feet from the North line and 660 feet from the West line

Section 33 Township 19S Range 25E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3483' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND
ABANDONMENT ☐

CASING

OTHER: Recomplete - Deepen / Cemetery Morrow ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

08/27/04...Set retainer at 7544' & squeezed Cisco Canyon Perfs @ 7650'-7726' (305 holes) with 400 sks RFC & 5 PPS D24 lead. Mixed at 14.2 PPG. Tailed with 200 sks Class H with 0.2% D167 & 2% D65. Mixed at 15.6 PPG.

08/31/04...Drilled retainer at 7544' and cement to 7827'.

09/02/04...Test csg to 1000# for 30 mins. POOH with tbg.

09/03/04...Perforate Morrow @ 9232'-40' (8'), 9244'-50' (6'), 9252'-57' (5'). Total 19' & 57 holes.

09/04/04...RIH w/tbg and swab test.

09/09/04...Frac perforations @ 9232'-40', 9244'-50' & 9252'-57' with 2000 gals 7 1/2% NeFe acid and 36,000 gals 40# 70Q Binary Foam with 41,180# 20/40 Interprop.

09/10/04...Put well on line.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kristi Green TITLE Hobbs Regulatory DATE 10/07/04

Type or print name Kristi Green Telephone No. 505-393-5905

(This space for State use)

APPROVED BY _____ TITLE _____ DATE OCT 12 2004
Conditions of approval, if any: FOR RECORDS ONLY