Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR. OIL COMS. DIV-DIST. DIV-DIST. DIV-DIST. DIV-DIST. DIV-DIST. DIV-DIST. DIV-DIST. PORM APPROVED BUREAU OF LAND MANAGEMENT 1 W. Grand Avenue Budget Bureau No. 1004-0135 Expires March 31, 1993 Artocia NIAA SOOHTLEase Designation and Serial N

SUNDRY NOTICES AND REPORTS ON WELLSSIA, NIVI 88. Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals		15 Lease Designation and Serial No. NMNM67709 6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		NA 7. If Unit or CA, Agreement Designation
1. Type of Well Oil Gas Other	RECEIVED	NMNM82522 8. Well Name and No.
2. Name of Operator DEVON ENERGY PRODUCTION COMPANY, LP. OCT 18 7004		MALAGA 1 FEDERAL COM 1
 Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 552-4615 Location of Well (Footage. Sec., T., R., M., or Survey Description) 990 FSL 2310 FWL, SEC1-T24S-R28E-UNIT LETTER O 		9. API Well No. 30-015-26249
		10. Field and Pool, or Exploratory Area PIERCE CROSSING; WOLFCAMP, NW (GAS) 11. County or Parish, State
		Eddy County, NM
	s) TO INDICATE NATURE OF NOTICE, REI	
TYPE OF SUBMISSION	TYPE OF ACTION	<u> </u>
Notice of Intent	Abandonment	Change of Plans
Cubacauart Barart	Recompletion Plugging Back	New Construction Non-Routine Fracturing
Subsequent Report	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
subsurface locations and measured and true vertical depth 1. Pull out existing 2-3/8" production to 2. Circulate hole with 9.0# Mud 3. Set CIBP at 9900'. Pump 50' cement 4. Pump 150' cement plug from 7850' 5. Pump 150' cement plug from 6270't 6. Cut 7" casing at 5000' and pull from 7. Set 150' cement plug from 4900' to 8. Set 150' cement plug from 2611' to 9. Set 150' cement plug from 406' to 5 10. Set 60' surface cement plug from 0'	abing and packer at 9868' from hole. It on top of CIBP. to 8000'. Tag cement. o 6420'. Tag cement. hole. 5050'. Tag cement. 2761'. Tag cement. 56'. Tag cement. to 60'. el. Set dry hole marker. Restore location.	APPROVED OCT 1 4 2004 LES BABYAK PETROLEUM ENGINEER
14. I hereby certify that the foregoing is true and correct	Ronnie STAGENERAL REQUIR	EMENTS AND ,
Signed Konnie Slack	Title Engineerin TechhAlan STIPULA	TIONS ATTACHETOU
This space for Federal or State office use)	THE ENGINEERING LEVERING OF THE OFFI	TALIAMINA LE CARLE SENSA.
Approved by	Title	Date
-	₹	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representation of any matter within its jurisdiction.



