

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87400  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources  
OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO.

30-015-32696

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Soapberry Draw "7" State

8. Well No.

1

9. Pool name or Wildcat

Undes. Catclaw Draw; Delaware,  
East

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Fasken Oil and Ranch, Ltd.

3. Address of Operator

303 W. Wall Ave., Suite 1800, Midland, TX 79701-5116

4. Well Location

Unit Letter K : 2100 feet from the south line and 1980 feet from the west line

Section 7

Township 21S

Range 26E

NMPM

County Eddy

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3271'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER:

☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: TD, set production casing ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Reached TD of 4000' on April 30, 2003 drilling a 7 7/8" hole. Ran 3998' of 5 1/2", 15.5#, J-55, LTC casing. Cemented with 425 sx Super C Modified (15#/sx Poz A and 11#/sx CSE) 5% salt and 1.1% FL-25 (s.w. 14.2ppg, yield 1.38 cu. ft./sx). Top of cement at 480' by temperature survey.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jimmy D. Carlile TITLE Regulatory Affairs Coordinator DATE 5/5/03

Type or print name Jimmy D. Carlile

Telephone No. (432) 687-1777

(This space for State use)

APPROVED BY Jim W. Brown

TITLE District Supervisor

DATE MAY 09 2003

Conditions of approval, if any: