

Submit 3 Copies To Appropriate District Office
 District I
 1628 N. French Dr., Hobbs, NM 88240
 District II
 811 South First, Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.
 30-015-04439

5. Indicate Type of Lease
 STATE ☐ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Tallmadge

7. Well No.

1

8. Pool name or Wildcat

Queen Grayburg San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN, OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter N : 990 feet from the South line and 1650 feet from the West line

Section 32 Township 17S Range 30E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Notify OCD 24 hrs. prior to any work done

Yates Petroleum Corporation proposes to plug and abandon this well as follows:

1. Rig up all H2S safety equipment. No casing recovery will be attempted.
2. TIH with tubing and tag CIBP with 35' cement at 2625'. Load the hole with plugging mud. Spot 25 sx Class "C" cement on top of CIBP.
3. TOH with tubing. Perforate 7" casing with 6 shots at 1250'. Perforate 7" casing with 6 shots at 545'.
4. TIH with WL and set cement retainer at 1150'. TIH with tubing and load the hole with plugging mud, sting into retainer and establish an injection rate. Squeeze with 60 sx Class "C" cement. Leave 35' cement on top of retainer. TOH with tubing.
5. TIH with WL and set cement retainer at 445'. TIH with tubing and load the hole with plugging mud, sting into retainer and establish circulation. Squeeze 60 sx Class "C" cement from 445' to 545'. Leave 35' cement on retainer. TOH with tubing.
6. ~~Spot 15 sx Class "C" cement plug at surface.~~ *Place 100' of Cmt. inside? outside of 7" & 8" csf. 0'-60'. WOC 24 HRS - TAG*
7. Remove all surface equipment and weld dry hole marker per regulations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE May 22, 2003

Type or print name Tina L. Huerta
 (This space for State use)

Telephone No. 505-748-1471

APPROVED BY [Signature]
 Conditions of approval, if any:

TITLE Field Rep ID DATE 5-29-03