

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1301 W. Central Avenue
Artesia, NM 88210

FORM APPROVED
OMB No. 1004-0135
Expires March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or re enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.

NM-81218

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.

Brannigan ANF Federal #1

9. API Well No.

30-015-10404

10. Field and Pool, or Exploratory Area

Indian Basin Upper Penn Assoc.

11. County or Parish, State

Eddy County, New Mexico

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well



Oil Well



Gas Well



Other

2. Name of Operator

Yates Petroleum Corporation

3a. Address

105 S. 4th Str., Artesia, NM 88210

3b. Phone No. (include area code)

505-748-1471

4. Location of Well (Footage, Sec., T., R., M., OR Survey Description)

660'FNL & 400'FWL of Section 6-T22S-R24E (Unit D, NWNW)

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other _____
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Yates Petroleum Corporation plans to plug and abandon this well as follows:

1. MIRU. Rig up safety equipment as needed. No casing recovery will be attempted.
2. Remove scale from 7" casing at +/-3020'-3100'.
3. Set 7" CIBP at 7380', spot 25 sx Class C cement plug from 7230'-7380', this well cover DV tool at 7321' and the Canyon top.
4. Spot 25 sx Class C cement plug from 6571'-6721' in the 7" casing across the Wolfcamp top.
5. Spot 25 sx Class C cement plug from 3970'-4120' in the 7" casing across the 2nd Bone Spring top.
6. Spot 25 sx Class C cement plug from 3014'-3164' in the 7" casing across the Bone Spring top.
7. Spot 50 sx Class C cement plug from 2180'-2477' in 7" casing across intermediate casing shoe. WOC. Tag plug, reset if necessary.
8. Spot 50 sx Class C cement plug from 379'-676' in 7" casing across the surface casing shoe and the San Andres top. WOC. Tag plug, reset if necessary.
9. Spot 25 sx Class C cement plug from 150' to surface. This will form the surface plug. WOC. Tag plug, reset if necessary.
10. Remove all surface equipment and weld dry hole marker per regulation.

NOTE: Yates Petroleum Corporation will use steel pits and no earth pits

14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Tina Huerta

Title

Regulatory Compliance Supervisor

Signature

Tina Huerta

Date

February 21, 2005

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

APPROVED

FEB 23 2005

LES BABYAK

PETROLEUM ENGINEER

Approved by

Approval of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant meets all requirements and those rights in the subject lease which would enable the applicant to conduct operations thereon.

Title

Date


Office

Special Stipulations Attached: Section 1782, Title 18, U.S.C. make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

WELL NAME: Brannigan ANF No. 1 FIELD: Indian Basin
 LOCATION: Unit D, 660' FNL & 440' FWL Sec 6-22S-24E Eddy County NM
 GL: 3935' ZERO: KB: 3946.5'
 SPUD DATE: COMPLETION DATE:
 COMMENTS: API # 30-015-27934
 Originally Drilled as the John H. Trigg's Federal IB # 1-6

CASING PROGRAM

13" 46#	626'
9-5/8" J-55 36# STC	2,427'
7" 26# N-80 889'	7,981'
7" 23# N-80 715'	
7" 26# J-55 1,817'	
7" 23# J-55 1,599'	
7" 20# J-55 2,901'	
7" 26# J-55 60'	



Before

TOPS:


San Andres	692'
Bone Spring Lime	3,164'
1 st Bone Spring	3,326'
2 nd Bone Spring	4,120'
3 rd Bone Spring	6,619'
Wolfcamp	6,721'
Canyon	7,414'

Not to Scale
 MH 2/7/05

WELL NAME: Brannigan ANF No. 1 FIELD: Indian Basin
 LOCATION: Unit D, 660' FNL & 440' FWL Sec 6-22S-24E Eddy County NM
 GL: 3935' ZERO: KB: 3946.5'
 SPUD DATE: COMPLETION DATE:
 COMMENTS: API # 30-015-27934
Originally Drilled as the John H. Trigg's Federal IB # 1-6

CASING PROGRAM

13" 46#	626'
9-5/8" J-55 36# STC	2,427'
7" 26# N-80	889'
7" 23# N-80	715'
7" 26# J-55	1,817'
7" 23# J-55	1,599'
7" 20# J-55	2,901'
7" 26# J-55	60'



TOPS:

San Andres	692'
Bone Spring Lime	3,164'
1 st Bone Spring	3,326'
2 nd Bone Spring	4,120'
3 rd Bone Spring	6,619'
Wolfcamp	6,721'
Canyon	7,414'