Submit 3 Copies 10 Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources		Form C-103 May 27, 2004
<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II			WELL API NO. 30-015-33409
1301 W. Grand Ave., Artesia, NM 88210 District III	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.		5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505			
(DO NOT USE THIS FORM FOR PROPOS DIFFERENT RESERVOIR. USE "APPLIC		OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name COATS COM
PROPOSALS.) 1. Type of Well: Oil Well	Gas Well X Other	RECEIVED	8. Well Number 1
2. Name of Operator GREAT WES	STERN DRILLING COMPA	NY NOV 1 9 2004	9. OGRID Number 009338
3. Address of Operator P.O. BOX		OGD:ARTESI	A10. Pool name or Wildcat ATOKA; PENN (GAS)
4. Well Location			
Unit Letter A : Section 19	feet from the No. Township 18-S		nMPM CountyEDDY
Section 19	11. Elevation (Show wheth		
Pit or Below-grade Tank Application 🔲 or	3,445' GR		
Pit typeDepth to Groundwa	terDistance from nearest	fresh water well Dist	ance from nearest surface water
Pit Liner Thickness: mil	Below-Grade Tank: Volume		nstruction Material
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF IN PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING	TENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPL	REMEDIAL WORI COMMENCE DRI	LLING OPNS. 🛛 P AND A
OTHER:	Г	OTHER:13 3/8" C	ASING X
13. Describe proposed or compl		te all pertinent details, and	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion
08/03/04 Notify Artesia OCD of spud. Spud well 4 p.m. 8/2/04. TD 17 ½" hole @ 6 a.m. 8/3/04. Drilling @ 525'. Run 12 jts of 13 3/8" 48# H-40, ST&C casing to 525 KBM with guide shoe & 4 centralizers. 1 half way on shoe jt & every 4th jt. Had to wash 11 jts down. RU Halliburton and cement w/lead cement 210 sk of Halliburton Light Premium Plus cement w/2% calcium chloride & .25lbm/sk Flocele. Tail w/240 sk Premium Plus cement w/2% calcium chloride. Plug down 3 p.m. 8/3/04. Circ. 35 sk to pit. Notify Mike with Artesia OCD. WOC 4 hrs cut off. NU well head & BOP. Run 12 ¼ bit & test BOP drilling cement, casing & plug to 600#, held OK.			
			•
			e and belief. I further certify that any pit or below- or an (attached) alternative OCD-approved plan
SIGNATURE Clan Robert	5 by HK TIT	LE PETROLEUM ENGIN	DATE 08/02/2004
Type or print name ALAN ROBERT For State Use Only	rs E-n	nail address:	Telephone No. (432)682-5241
	R RECORDS ONE	LE	NOV 3 2 2004