

ATS-11-537

OCD-ARTESIA

Form 3160-3  
(April 2004)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED  
OMB No. 1004-0137  
Expires March 31, 2007

1a. Type of work <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5 Lease Serial No. <b>NMLC-029415B</b>
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6 If Indian, Allottee or Tribe Name N/A
2 Name of Operator <b>COG Operating LLC</b> <i>&lt;229137&gt;</i>		7 If Unit or CA Agreement, Name and No N/A
3a. Address <b>550 W. Texas Ave., Suite 1300 Midland, TX 79701</b>	3b. Phone No. (include area code) <b>432-685-4384</b>	8. Lease Name and Well No. <b>Pucker 13 #43</b> <i>&lt;38660&gt;</i>
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface <b>1650' FNL &amp; 1650' FEL, UL G</b> At proposed prod. zone		9 API Well No. <b>30-015-39180</b>
14 Distance in miles and direction from nearest town or post office* <b>9 miles East of Loco Hills, NM</b>		10 Field and Pool, or Exploratory <b>Fren; Glorieta-Yeso, East</b> <i>&lt;26770&gt;</i>
15 Distance from proposed* location to nearest property or lease line, ft (Also to nearest drig unit line, if any) <b>1650'</b>		11. Sec, T R. M or Blk and Survey or Area <b>Sec 13 T17S R31E</b>
16 No of acres in lease <b>1920</b>		12 County or Parish <b>EDDY</b>
17. Spacing Unit dedicated to this well <b>40</b>		13. State <b>NM</b>
18 Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft <b>100'</b>		
19 Proposed Depth <b>7000'</b>		
20 BLM/BIA Bond No. on file <b>NMB000215</b>		
21 Elevations (Show whether DF, KDB, RT, GL, etc.) <b>3945' GL</b>		
22 Approximate date work will start* <b>04/30/2011</b>		
23 Estimated duration <b>15 days</b>		

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No 1, shall be attached to this form

- |   |  |
|---|--|
| 1 Well plat certified by a registered surveyor.   | 4 Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).     |
| 2 A Drilling Plan   | 5. Operator certification  |
| 3 A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office) | 6. Such other site specific information and/or plans as may be required by the authorized officer. |

25 Signature <i>Kelly J. Holly</i>	Name (Printed/Typed) <b>Kelly J. Holly</b>	Date <b>02/09/2011</b>
Title <b>Permitting Tech</b>		

Approved by (Signature) <b>/s/ Don Peterson</b>	Name (Printed/Typed)	Date <b>JUN - 2 2011</b>
Title <b>FIELD MANAGER</b>	Office <b>CARLSBAD FIELD OFFICE</b>	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.


APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

\*(Instructions on page 2)

Roswell Controlled Water Basin

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL



APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS  
AND SPECIAL STIPULATIONS  
ATTACHED

## MASTER DRILLING PROGRAM

### 1. Geologic Name of Surface Formation

Quaternary

### 2. Estimated Tops of Important Geologic Markers:

Quaternary	Surface
Rustler	518'
Top of Salt	560'
Base of Salt	1150'
Yates	1830'
Seven Rivers	2190'
Queen	2830'
Grayburg	3240'
San Andres	3580'
Glorietta	5080'
Paddock	5125'
Blinbry	5590'
Tubb	6580'

### 3. Estimated Depths of Anticipated Fresh Water, Oil and Gas

Water Sand	150'	Fresh Water
Grayburg	3240'	Oil/Gas
San Andres	3580'	Oil/Gas
Glorieta	5080'	Oil/Gas
Paddock	5125'	Oil/Gas
Blinebry	5590'	Oil/Gas
Tubb	6580'	Oil/Gas

*see COA*

*see COA* No other formations are expected to give up oil, gas or fresh water in measurable quantities. Setting 13 3/8" casing to ~~450'~~ and circulating cement back to the surface will protect the surface fresh water sand. The Salt Section will be protected by setting 8 5/8" casing to ~~1800'~~ and circulating cement, in a single or multi-stage job and/or with an ECP, back to the surface. Any shallower zones above TD, which contain commercial quantities of oil and/or gas, will have cement circulated across them. This will be achieved by cementing, with a single or multi-stage job, the 5 1/2" production casing back 200' into the intermediate casing, (but calculated to surface) to be run at TD. If wellbore conditions arise that require immediate action and/or a change to this program, COG Operating LLC personnel will always react to protect the wellbore and/or the environment. *see COA*

#### 4. Casing Program

Hole Size	Interval	OD Casing	Weight	Grade	Jt., Condition	Jt.	burst/collapse/tension
17 1/2" <del>735</del>	0- <del>450</del>	13 3/8"	48#	H-40orJ-55	New	ST&C	8.71/3.724/14.91
11" <del>2135</del>	0- <del>1800</del>	8 5/8"	24or32#	J-55	New	ST&C	2.91/1.46/5.65
7 7/8"	0-T.D.	5 1/2"	15.5 or 17#	J-55orL80	New	LT&C	1.71/1.574/2.20

#### 5. Cement Program

13 3/8" Surface Casing:

Class C, 475 sx w/ 2% CaCl<sub>2</sub>, 0.25 pps CF, yield-1.32, back to surface 100% excess

See  
COA

8 5/8" Intermediate Casing:

##### 11" Hole:

**Single Stage:** LEAD 350 sx 50:50:10 C:Poz:Gel w/ 5% Salt +0.25% CF, yield-2.45 + TAIL 200 sx Class C w/2% CaCl<sub>2</sub>, yield-1.32, back to surface. 145% excess

**Multi-Stage:** Stage 1: 350 sx Class C, w/2% CaCl<sub>2</sub>, yield - 1.32. 40% excess  
Stage 2: 200 sx Class C w/2% CaCl<sub>2</sub>, yield - 1.32, back to surface, 108% excess  
Multi stage tool to be set at approximately, depending on hole conditions, 500' (50' below the surface casing). Cement volumes will be adjusted proportionately for depth changes of multi stage tool.

See  
COA

See  
COA

5 1/2" Production Casing:

**Single Stage:** LEAD 500 sx 35:65:6 C:Poz:Gel w/ 5% Salt + 5 pps LCM + 0.2% SMS + 0.3% FL-52A + 0.125 pps CF, yield-2.05 + TAIL 400 sx 50:50:2 C:Poz:Gel w/ 5% Salt + 3 pps LCM + 0.6% SMS + 1% FL-25 + 1% BA-58 + 0.3% FL-52A + 0.125 pps CF, yield-1.37, to 200' minimum tie back to intermediate casing. 44.4% open hole excess, cement calculated back to surface.

**Multi-Stage:** Stage 1: (Assumed TD of 6700') 500 sx 50:50:2, C:Poz:Gel w/ 5% Salt + 3 pps LCM + 0.6% SMS + 1% FL-25 + 1% BA-58 + 0.3% FL-52A + 0.125 pps CF, yield - 1.37, 7% excess; minimum volume, will be adjusted up after caliper is

See  
COA

run. Stage 2: LEAD 450 sx 50:50:2  
C:Poz:Gel w/ 5% Salt + 3 pps LCM + 0.6%  
SMS + 1% FL-25 + 1% BA-58 + 0.3% FL-  
52A + 0.125 pps CF, yield - 1.37, + TAIL  
250 sx Class C w/ 0.3% R-3 + 1.5% CD-32,  
yield - 1.02 152% open hole excess, cement  
calculated back to surface. Multi stage tool  
to be set at approximately, depending on  
hole conditions, 3000'. Cement volumes  
will be adjusted proportionately for depth  
changes of multi stage tool, assumption for  
tool is water flow.

## 6. Minimum Specifications for Pressure Control

The blowout preventer equipment (BOP) shown in Exhibit #9 will consist of a double ram-type (2000 psi WP) preventer, and in some cases possibly a 2000 psi Hydril type annular preventer as provided for in Onshore Order #2. This unit will be hydraulically operated and the ram type preventer will be equipped with blind rams on top of 4 1/2" drill pipe rams on the bottom. A 13-5/8" or 11" BOP will be used, depending on the rig selected, during the drilling of the well. The BOP will be nipped up on the 13 3/8" surface casing with BOP equipment and tested to 2000 psi. When 11" BOP is used the special drilling flange will be utilized on the 13-3/8" head to allow testing the BOP with a retrievable test plug. After setting 8-5/8" the BOP will then be nipped up on the 8 5/8" intermediate casing and tested by a third party to 2000 psi and used continuously until total depth is reached. Pipe rams will be operationally checked each 24-hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment (Exhibit #10) will include a Kelly cock and floor safety valve, choke lines and a choke manifold (Exhibit #11) with a 2000 psi WP rating.

The majority of the rigs currently in use have a 13-5/8" BOP, so no special provision is needed for most wells in the area for conventionally testing the BOP with a test plug. However, due to the vagaries of rig scheduling, it might be that one of the few rigs with 11" BOP's might be called upon to drill any specific well in the area. Note that intermediate hole size is always 11". Therefore, COG Operating LLC respectfully requests a variance to the requirement of 13-5/8" BOP on 13-3/8" casing. When that circumstance is encountered the special flange will be utilized to allow testing the entire BOP with a test plug, without subjecting the casing to test pressure. The special flange also allows the return to full-open capability if desired.

See  
COA

**7. Types and Characteristics of the Proposed Mud System**

The well will be drilled to TD with a combination of brine, cut brine and polymer mud system. The applicable depths and properties of this system are as follows:

See COA

DEPTH	TYPE	WEIGHT	VISCOSITY	WATERLOSS
0-450' <del>735'</del>	Fresh Water	8.5	28	N.C.
450-1800' <del>2135'</del>	Brine	10	30	N.C.
1800'-TD	Cut Brine	8.7-9.1	29	N.C.

Sufficient mud materials will be kept at the well site to maintain mud properties and meet minimum lost circulation and weight increase requirements at all times.

**8. Auxiliary Well Control and Monitoring Equipment**

- A. Kelly cock will be kept in the drill string at all times.
- B. A full opening drill pipe-stabbing valve with proper drill pipe connections will be on the rig floor at all times.

**9. Logging, Testing and Coring Program** See COA

- A. The electric logging program will consist of GR-Dual Laterolog, Spectral Density, Dual Spaced Neutron, CSNG Log and will be run from TD to 8 5/8" casing shoe.
- B. Drill Stem test is not anticipated.
- C. No conventional coring is anticipated.
- D. Further testing procedures will be determined after the 5 1/2" production casing has been cemented at TD, based on drill shows and log evaluation.

**10. Abnormal Conditions, Pressure, Temperatures and Potential Hazards**

No abnormal pressures or temperatures are anticipated. The estimated bottom hole at TD is 110 degrees and the estimated maximum bottom hold pressure is 2300 psig. Measurable gas volumes or Hydrogen Sulfide levels have not been encountered during drilling operations in this area, although a Hydrogen Sulfide Drilling Operation Plan is attached to this program. No major loss of circulation zones has been reported in offsetting wells.


**11. Anticipated Starting Date and Duration of Operations**

Road and location work will not begin until approval has been received from the BLM. As this is a Master Drilling plan, please refer to the Form 3160-3 for the anticipated start date. Once commenced, drilling operations should be finished in approximately 12 days. If the well is productive, an additional 30 days will be required for completion and testing before a decision is made to install permanent facilities.


# COG Operating LLC

## Exhibit #9

### BOPE and Choke Schematic



Choke Manifold Requirement (2000 psi WP)  
No Annular Required



**NOTES REGARDING THE BLOWOUT PREVENTERS**

**Master Drilling Plan  
Eddy County, New Mexico**

1. Drilling nipple to be so constructed that it can be removed without use of a welder through rotary table opening, with minimum I.D. equal to preventer bore.
2. Wear ring to be properly installed in head.
3. Blow out preventer and all fittings must be in good condition, 2000 psi WP minimum.
4. All fittings to be flanged.
5. Safety valve must be available on rig floor at all times with proper connections, valve to be full 2000 psi WP minimum.
6. All choke and fill lines to be securely anchored especially ends of choke lines.
7. Equipment through which bit must pass shall be at least as large as the diameter of the casing being drilled through.
8. Kelly cock on Kelly.
9. Extension wrenches and hands wheels to be properly installed.
10. Blow out preventer control to be located as close to driller's position as feasible.
11. Blow out preventer closing equipment to include minimum 40-gallon accumulator, two independent sources of pump power on each closing unit installation all API specifications.



DISTRICT I --- CHECKLIST FOR INTENTS TO DRILL

Operator COG OPERATING LLC OGRID # 229137  
 38660 Well Name & # BUCKETT 13 # 43 Surface Type (F) (S) (P)  
 Location: UL G, Sect 13, Twnship 17 s, RNG 31 e, Sub-surface Type (F) (S) (P)

A. Date C101 rec'd      /      /      C101 reviewed      /      /     

B. 1. Check mark, Information is OK on Forms:

OGRID X BONDING FED PROP CODE X WELL #     , SIGNATURE     

2. Inactive Well list as of: 7/5/11 # wells 2915, # Inactive wells 8

a. District Grant APD but see number of inactive wells:

No letter required X; Sent Letter to Operator     , to Santa Fe     

3. Additional Bonding as of: 7/5/11

a. District Denial because operator needs addition bonding:

No Letter required X; Sent Letter to Operator     , To Santa Fe     

b. District Denial because of Inactive well list and Financial Assurance:

No Letter required X; Sent Letter to Operator     , To Santa Fe     

C. C102 YES X NO     , Signature X

1. Pool FREN-GUARIETA-YEHO, Code 26770

a. Dedicated acreage 40, What Units     

b. SUR. Location Standard X; Non-Standard Location     

c. Well shares acres: Yes     , No X, # of wells      plus this well #     

2. 2<sup>nd</sup>. Operator in same acreage, Yes     , No X

Agreement Letter     , Disagreement letter     

3. Intent to Directional Drill Yes     , No X

a. Dedicated acreage     , What Units     

b. Bottomhole Location Standard     , Non-Standard Bottomhole     

4. Downhole Commingle: Yes     , No X

a. Pool #2     , Code     , Acres     

Pool #3     , Code     , Acres     

Pool #4     , Code     , Acres     

5. POTASH Area Yes     , No X

D. Blowout Preventer Yes X, No     

E. H2S Yes X, No     

F. C144 Pit Registration Yes     , No     , need

G. Does APD require Santa Fe Approval:

1. Non-Standard Location: Yes     , No X, NSL #     

2. Non-Standard Proration: Yes     , No X, NSP #     

3. Simultaneous Dedication: Yes     , No X, SD #     

Number of wells      Plus #     

4. Injection order Yes     , No X; PMX #      or WFX #     

5. SWD order Yes     , NO X; SWD #     

6. DHC from SF     ; DHC-HOB     ; Holding     

7. OCD Approval Date      /      /     

API #30-0 15 -- 39180

8. Reviewers