Font 3160-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD	Artesia
-----	---------

FORM APPROVED OMB NO. 1004-0135 Expures: July 31, 2010

Expires: July 31, 2010

NMNM016786

INDRY	NOTICES		<b>REPORTS</b>	ON	WELLS
,,45,,,	11011000	$\neg$	11-1 -1110	9.4	***

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

6 If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7 If Unit or CA/Agreement, Name and/or No				
1. Type of Well					8 Well Name and No. SABER FEDERAL 1				
Oil Well Gas Well Oth	TILO				· · · · · · · · · · · · · · · · · · ·				
2 Name of Operator COG OPERATING LLC	rator Contact KANICIA CASTILLO RATING LLC E-Mail: kcastillo@conchoresources.com					9 API Well No 30-015-27882			
3a. Address 550 WEST TEXAS AVE STE MIDLAND, TX 79701	3b Phone No. Ph: 432-68	(include area cod 5-4332	de)	10 Field and Pool, or Exploratory SWD;UPPER PENN					
4 Location of Well (Footage, Sec., 7	, R, M, or Survey Description	1)			11 County or Parish, and State				
Sec 11 T17S R29E 720FNL 2				EDDY COUNTY, NM					
12. CHECK APPI	ROPRIATE BOX(ES) TO	) INDICATE	NATURE OF	NOTICE, R	EPORT, OR	OTHER	DATA	•	
TYPE OF SUBMISSION	TYPE OF ACTION								
Notice of Intent	☐ Acidize ☐ Deepen		en	Production (Start/Resume)		sume)	Water Shut-Off		
□ Notice of Intent	Alter Casing	□ Fract	ure Treat	Reclamation			₩ell Integrity		
Subsequent Report	☐ Casing Repair	□ New	Construction	☐ Recom	olete		Other		
☐ Final Abandonment Notice	☐ Change Plans	Plug	and Abandon	Tempor	arily Abando	n	_		
	Convert to Injection	□ Plug	Back	□ Water I	Disposal				
testing has been completed. Final Al determined that the site is ready for f 4/26/11 MIRU. 4/27/11 POOH w/ prod pkr. 4/28/11 Clean out to PBTD @ 5/02/11 RIH w/3-1/2 IPC tbg a for 30min. Good test.	inal inspection )  9333.				,	R	ECEIV JUL 15 20	ED	
5/04/11 Perform MIT for NM C Acidized w/5700 gals 15% 90	550 psi for 30 d Equip. RDM	0 min. Passed test. 10.			NMOCD ARTESIA				
SEE ATTACHED CONDITIONS OF	APPROVAL	Acce	pted for rec NMOCD / 7/2/11	cord &	ccept idd Co. PR La	for rec	cord, 04/23/201	(/	
14 Thereby certify that the foregoing is	Electronic Submission #	108648 verified PERATING LL	by the BLM W C, sent to the (	ell Informatio	n System				
Name(Printed/Typed) KANICIA	CASTILLO		Title PREP	ARER	ACCE	PTED	FOR REC	ORI	
Signature (Electronic S	Submission)		Date 05/19/	2011				]	
	THIS SPACE FO	R FEDERA	OR STATE	OFFICE U	E	JUN 2	4 2011		
Approved By Conditions of approval, if any, are attached that the applicant holds lead or ex-	d - Approval of this notice does	not warrant or	Title				ND MANAGEN FIELD OFFICE		
certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office		L			;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;	

## Conditions of Approval: Wells with Packers\*

## COG Operating LLC Saber Federal 1

June 23, 2011

- Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within 30 days.
  - a. The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
  - b. Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
  - c. Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822.
  - d. Submit a subsequent Sundry Form 3160-5 relating the MIT activity. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
  - e. Use of tubing internal protection, on/off tubing equipment just above the packer, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore work.
  - f. Submit the original subsequent sundry with three copies to BLM Carlsbad.
- 2. Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
  - a. Approved injection pressure compliance is required.
  - b. If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
  - c. When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
  - i. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment.
  - e. Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.

- 3. The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
  - a. The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
  - b. Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
  - c. Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer (Paul R. Swartz at 575-200-7902). If there is no response, notify the BLM on call drilling phone, 575-361-2822.
  - d. Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for approval by BLM and NMOCD with a detailed plan for correction and the anticipated date of correction. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days.
  - e. After the repairs submit a (Sundry Form 3160-5) Subsequent report, describing the repair(s) and Mechanical Integrity Test as per item 1 above.
  - f. The operator shall keep accurate and current records documenting that the casing annulus is fluid filled. A suggested format for these records is available from the BLM Carlsbad Field Office. Copies of those records shall be furnished at the request of a BLM authorized officer.

\*COA's prepared by Paul R. Swartz