

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.

30-015-37239

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name

Sausage SWD

8. Well Number #1

9. OGRID Number

229137

10. Pool name or Wildcat

Delaware

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other SWD

2. Name of Operator

COG Operating, LLC

3. Address of Operator

2208 W. Main Street Artesia, NM 88210

4. Well Location

Unit Letter G : 2310 feet from the N line and 1650 feet from the E lineSection 7 Township 25S Range 30E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3117' GR

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☐OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/24/20 MIRU plugging equipment. Dug out cellar. 03/25/20 NDBOP. Could not unset packer. OCD & COG approved to leave packer in hole. POH w/ 138 jts of 3 1/2" tbg. Set 5 1/2" CIBP @ 4395'. Circulated hole w/ brine H2O. Pressure tested csg, held 700 PSI. 03/26/20 Circulated hole w/ MLF. Spotted 25 sx class C cmt w/ 2% CACL @ 4395-4126'. WOC. Tagged plug @ 4140'. Perf'd csg @ 3500'. Pressured up on perfs. Spotted 25 sx class C cmt @ 3550-3297'. WOC. 03/27/20 Tagged plug @ 3290'. Perf'd csg @ 880'. Established an injection rate of 1 BPM @ 500 PSI. Sqz'd 50 sx class C cmt w/ 2% CACL @ 880-670'. WOC. Tagged plug @ 658'. Perf'd csg @ 100'. NDBOP, Sqz'd 30 sx class C cmt @ 100' & circulated to surface on 5 1/2" & 8 5/8" csg. 03/30/20 Topped off well with 5 sx cmt @ surface on 5 1/2" & 8 5/8" csg. Rigged down & moved off. 04/01/20 Moved in backhoe and welder, dug out cellar, cut off well head, and Gilbert Cordero w/ OCD verified cement to surface. Welded on "Above Ground Dry Hole Marker". Backfilled cellar, cut off deadmen, cleaned location, and moved off.

Spud Date:

Rig Release Date:

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, [www.emnrd.state.nm.us](http://www.emnrd.state.nm.us)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Delilah Flores TITLE: Regulatory Technician

DATE: 4/2/2020

Type or print name: Delilah Flores

E-mail address: [dflores2@concho.com](mailto:dflores2@concho.com)

PHONE: 575-308-7264

**For State Use Only**APPROVED BY: Gilbert Cordero TITLE: Staff Mgr DATE: 4/9/20

Conditions of Approval (if any):