

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.***SUBMIT IN TRIPLICATE - Other instructions on page 2**

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		5. Lease Serial No. NMNM004825
2. Name of Operator MEWBOURNE OIL COMPANY		6. If Indian, Allottee or Tribe Name
Contact: JACKIE LATHAN E-Mail: jlathan@mewbourne.com		7. If Unit or CA/Agreement, Name and/or No. NMNM109705
3a. Address P O BOX 5270 HOBBS, NM 88241	3b. Phone No. (include area code) Ph: 575-393-5905 Fx: 575-393-5905	8. Well Name and No. NORMANDY 31/32 WOMP FED COM 11
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 31 T20S R29E 2520FSL 365FWL 32.529606 N Lat, 104.121628 W Lon		9. API Well No. 30-015-46689-00-X1
		10. Field and Pool or Exploratory Area RED HILLS
		11. County or Parish, State EDDY COUNTY, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Well Spud
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

04/02/2020

Spud 26" hole @ 377'. Ran 377' of 20" 94# J55 BT&C csg. Cmt w/600 sks Class C w/additives. Mixed w/12.5#/g w/2.14 yd. Displaced w/124 bbls of BW. Plug down @ 12:00 A.M. 04/03/20. Circ 317 sks of cmt to the pits. Drilled out with 17 ?? bit.

04/05/2020

TD 'ed 17 1/2" hole @ 1368'. Ran 1353' of 13 3/8" 54.5# J55 ST&C csg. Cmt w/850 sks Class C w/additives. Mixed w/13.5#/g w/1.77 yd. Displaced w/203 bbls of BW. Plug down @ 11:45 A.M. 04/05/20. Did not circ cmt. Lost circ w/43 bbls left to displace. Lift pressure of 350# @ 3 BPM. Ran temp surv indication TOC @ 270?. TIH with 1? pipe. Tag @ 355?. Ran 1? pipe in 3 stages with 400 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.77 yd. Circ 125 sks of cmt to surface. Test BOPE to 5000# & Annular to 3500#. At 10:00 P.M. 04/06/20, tested csg to 1500# for 30 mins, held OK. FIT to

14. I hereby certify that the foregoing is true and correct. Electronic Submission #513072 verified by the BLM Well Information System For MEWBOURNE OIL COMPANY, sent to the Carlsbad Committed to AFMSS for processing by PRISCILLA PEREZ on 04/28/2020 (20PP2470SE)	
Name (Printed/Typed) RUBY CABALLERO	Title CLERK
Signature (Electronic Submission)	Date 04/28/2020

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By ACCEPTED	JONATHON SHEPARD Title PETROLEUM ENGINEER	Date 05/07/20
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office Carlsbad

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

Entered 05/12/2020 - KMS NMOCD

Additional data for EC transaction #513072 that would not fit on the form

32. Additional remarks, continued

9.5 PPG EMW. Drilled out with 12 1/4" bit.

Temp surv, charts & Schematic attached.

04/07/2020

TD'ed 12 1/4" hole @ 3052?. Ran 3037' of 9 5/8" 40# HCL80 LT&C Csg. Cmt 1st stage lead w/675 sks Class C w/additives. Mixed @ 13.5#/g w/1.77 yd. Tail w/200 sks Class C w/0.1% Retarder. Mixed @ 14.8#/g w/1.33 yd. Displace w/227 bbls of FW. Plug down @ 11:00 A.M. 04/08/20. Set ACP w/3000#. Circ 171 sks of cmt to the pits. Drop cancellation bomb & cycle DV tool to closed position w/2200#. Set Cameron Mandrel hanger through BOP w/105k#. At 2:30 A.M. 04/09/20, tested csg to 1500# for 30 mins, held OK. FIT test to EMW of 10.0 PPG. Drilled out with 8 3/4" bit.

04/14/2020

TD'ed 8 3/4" hole @ 9790?. Ran 9775' of 7" 29# HCP110 LT&C csg. Cmt w/625 sks 50:50 Poz w/additives. Mixed @ 11.5#/g w/2.27 yd. Tail w/400 sks Class H w/additives. Mixed @ 14.5#/g w/1.11 yd. Displaced w/362 bbls OBM. Plug down @ 6:00 P.M. 04/14/20. Circ 25 sks of cmt to the pits. Set Cameron mandrel hanger through BOP w/160k#. At 8:15 P.M. 04/15/20, tested csg to 1500# 30 mins, held OK. FIT test to 11.5 PPG EMW. Drilled out with 6 1/8" bit.

Bond on file: NM1693 nationwide & NMB000919

Revisions to Operator-Submitted EC Data for Sundry Notice #513072

	Operator Submitted	BLM Revised (AFMSS)
Sundry Type:	SPUD NOI	SPUD NOI
Lease:	NMNM004825	NMNM004825
Agreement:		NMNM109705 (NMNM109705)
Operator:	MEWBOURNE OIL COMPANY PO BOX 5270 HOBBS, NM 88241 Ph: 575-393-5905	MEWBOURNE OIL COMPANY P O BOX 5270 HOBBS, NM 88241 Ph: 575.393.5905
Admin Contact:	JACKIE LATHAN AUTHORIZED REPRESENTATIVE E-Mail: jlathan@mewbourne.com Ph: 575-393-5905	JACKIE LATHAN AUTHORIZED REPRESENTATIVE E-Mail: jlathan@mewbourne.com Ph: 575-393-5905 Fx: 575-393-5905
Tech Contact:	RUBY CABALLERO REGULATORY E-Mail: rcaballero@mewbourne.com Ph: 575-393-5905 Ext: 5032	RUBY CABALLERO CLERK E-Mail: rojeda@mewbourne.com Ph: 575-393-5905
Location: State: County:	NM EDDY	NM EDDY
Field/Pool:	RED HILLS BONE SPRING	RED HILLS
Well/Facility:	NORMANDY 31/32 W0MP FED COM 1H Sec 31 T20S R29E Mer NMP SWSW 2520FSL 365FWL	NORMANDY 31/32 W0MP FED COM 1H Sec 31 T20S R29E 2520FSL 365FWL 32.529606 N Lat, 104.121628 W Lon