

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

NMOCD-REC'D: 5/27/2020 Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office
☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT AS-DRILLED PLAT

¹ API Number 30-015-44305	² Pool Code 98220	³ Pool Name PURPLE SAGE; WOLFCAMP
⁴ Property Code 317790	⁵ Property Name REMUDA NORTH 25 STATE	⁶ Well Number 168H
⁷ OGRID No. 005380	⁸ Operator Name XTO ENERGY, INC.	⁹ Elevation 3,072'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
I	25	23 S	29 E		2,380	SOUTH	705	EAST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	24	23 S	29 E		223	NORTH	657	EAST	EDDY

¹² Dedicated Acres 480	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.
NOTE: AS-DRILLED BOTTOM HOLE PLOTTED FROM
DATA FURNISHED BY XTO ENERGY

¹⁶ SEC. 13 T23S R29E SEC. 18 T23S R30E SEC. 19 T23S R30E SEC. 24 T23S R29E SEC. 25 T23S R29E SEC. 30 T23S R30E SEC. 31 T23S R30E SEC. 36 T23S R29E	GEODETIC COORDINATES NAD 27 NME SURFACE LOCATION Y= 463,989.5 X= 624,232.8 LAT.= 32.274984°N LONG.= 103.931373°W FIRST TAKE POINT NAD 27 NME Y= 464,620.6 X= 624,265.0 LAT.= 32.276719°N LONG.= 103.931261°W CORNER COORDINATES TABLE NAD 27 NME A - Y= 464,258.3 N, X= 624,936.3 E B - Y= 464,258.9 N, X= 623,667.2 E C - Y= 466,919.4 N, X= 624,926.4 E D - Y= 466,919.6 N, X= 623,603.9 E E - Y= 469,568.1 N, X= 624,904.6 E F - Y= 469,570.2 N, X= 623,580.9 E G - Y= 472,226.1 N, X= 624,885.4 E H - Y= 472,227.8 N, X= 623,559.3 E KICK OFF POINT NAD 83 NME Y= 463,973.2 X= 665,508.9 LAT.= 32.274898°N LONG.= 103.931563°W KICK OFF POINT NAD 27 NME Y= 463,913.8 X= 624,325.9 LAT.= 32.274775°N LONG.= 103.931072°W LAST TAKE POINT NAD 27 NME Y= 471,865.7 X= 624,227.1 LAT.= 32.296635°N LONG.= 103.931296°W BOTTOM HOLE LOCATION NAD 27 NME Y= 472,003.7 X= 624,230.0 LAT.= 32.297015°N LONG.= 103.931285°W GEODETIC COORDINATES NAD 83 NME SURFACE LOCATION Y= 464,048.9 X= 665,415.8 LAT.= 32.275107°N LONG.= 103.931863°W FIRST TAKE POINT NAD 83 NME Y= 464,680.0 X= 665,448.0 LAT.= 32.276841°N LONG.= 103.931752°W CORNER COORDINATES TABLE NAD 83 NME A - Y= 464,317.7 N, X= 666,119.3 E B - Y= 464,318.3 N, X= 664,850.2 E C - Y= 466,978.9 N, X= 666,109.3 E D - Y= 466,979.1 N, X= 664,786.8 E E - Y= 469,627.6 N, X= 666,087.4 E F - Y= 469,629.7 N, X= 664,763.7 E G - Y= 472,285.7 N, X= 666,068.1 E H - Y= 472,287.4 N, X= 664,742.0 E LAST TAKE POINT NAD 83 NME Y= 471,925.3 X= 665,409.8 LAT.= 32.296758°N LONG.= 103.931787°W BOTTOM HOLE LOCATION NAD 83 NME Y= 472,063.3 X= 665,412.7 LAT.= 32.297137°N LONG.= 103.931776°W	¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Cheryl Rowell</i> 05/26/20 Signature Date Cheryl Rowell Printed Name cheryl_rowell@xtoenergy.com E-mail Address ¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 4-22-2020 Date of Survey Signature and Seal of Professional Surveyor: <i>[Signature]</i> MARK DILLON HARP 23786 Certificate Number JC 2019010071
--	---	--

Intent ☐ As Drilled ☒

API # 30-015-44305			
Operator Name: XTO ENERGY INC		Property Name: REMUDA NORTH 25 STATE	Well Number 168H

Kick Off Point (KOP)

UL I	Section 25	Township 23S	Range 29E	Lot	Feet 2304	From N/S South	Feet 612	From E/W East	County Eddy
Latitude 32.274898					Longitude 103.931261				NAD 83

First Take Point (FTP)

UL H	Section 25	Township 23S	Range 29E	Lot	Feet 2299	From N/S North	Feet 670	From E/W East	County Eddy
Latitude 32.276841					Longitude 103.931752				NAD 83

Last Take Point (LTP)

UL A	Section 24	Township 23S	Range 29E	Lot	Feet 361	From N/S North	Feet 661	From E/W East	County Eddy
Latitude 32.296758					Longitude 103.931787				NAD 83

Is this well the defining well for the Horizontal Spacing Unit? ☐

Is this well an infill well? ☐

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API # 30-015-44232			
Operator Name: XTO ENERGY INC.		Property Name: REMUDA NORTH 25 STATE	Well Number 105H

KZ 06/29/2018



November 25, 2019

New Mexico Energy, Minerals and Natural Resources Department
Attn: Oil Conservation Division
1220 South St. Francis Drive
Santa Fe, NM 87505


Attn: Colin Gilmore

Re: XTO Energy Inc.
Remuda North 25 State #168H
Purple Sage; Wolfcamp
Eddy County, New Mexico
API# 30-015-44305

Enclosed please find the original and one (1) copy of the survey performed on the reference well by STRYKER ENERGY DIRECTIONAL SERVICES, LLC. (P-5 #828149) Other information required by your office is as follows:

<u>Name & Title</u>	<u>Drainhole No.</u>	<u>Survey Depths</u>	<u>Dates Performed</u>	<u>Type Survey</u>
Cliff Bray	Original Hole	157ft. to 19,122ft.	09-02-19 to 10-10-19	MWD Survey

A certified plat on which the bottom-hole location is oriented to both surface location and to the lease lines (or unit lines in case of pooling) is attached to the survey report. If any other information is required, please contact the undersigned at the letterhead address and phone number.


Eric Estes

Enclosures

CC: XTO Energy Inc.
Attn: Trey Peroyea
6401 Holiday Hill Rd. #5
Midland, Texas 79707

NMEMaNRD\ XTO Energy Inc.\Remuda North 25 State #168H\M191132

STRYKER ENERGY DIRECTIONAL SERVICES, LLC.
P.O. Box 1250
Montgomery, TX 77356
Office (936) 582-7296 * Fax (936)-588-4163



November 25, 2019

Survey Certification Report

STATE OF TEXAS

COUNTY OF Montgomery

I, Eric Estes, certify that I am employed by STRYKER ENERGY DIRECTIONAL SERVICES, L.L.C., and that I did on the day(s) of September 2, 2019 through October 10, 2019, conduct or supervise the taking of a SEDS MWD Original Hole Survey from a depth of 157feet to a depth of 19,122feet; that I am authorized and qualified to make this report; that this survey was conducted at the request of XTO Energy Inc., for the Remuda North 25 State #168H well, API #30-015-44305 in Eddy County, New Mexico; and that I have reviewed this report and find that it conforms to the principles as set forth by STRYKER ENERGY DIRECTIONAL SERVICES, L.L.C..

A handwritten signature in black ink, appearing to read "Eric Estes", is written over a horizontal line.

Eric Estes

STRYKER ENERGY DIRECTIONAL SERVICES, L.L.C.

**STRYKER ENERGY DIRECTIONAL SERVICES, LLC.
P.O. Box 1250
Montgomery, TX 77356
Office (936) 582-7296 * Fax (936)-588-4163**

Survey Report Landscape

Company: XTO Energy
 Project: Eddy County, NM (NAD27) NMEZ Grid
 Site: Remuda North 25 State 107H, 127H, 128H, 168H, 908H
 Well: RN25-168H
 Wellbore: 168H Lateral
 Design: 168H Lateral AsDrilled

Local Co-ordinate Reference:
 TVD Reference: 3074+25 @ 3099.00usft (Tr1101)
 MD Reference: 3074+25 @ 3099.00usft (Tr1101)
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature
 Database: STRYKER_EDM

Survey Program		Date	10/11/19		
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
157.00	10,677.00	Survey #1 (168H Lateral)	MWD	OWSG MWD - Standard	
10,722.00	19,122.00	Survey #2 (168H Lateral)	MWD+IFR1+MS	OWSG MWD + IFR1 + Multi-Station Correction	
19,173.00	19,173.00	Survey #3 (168H Lateral)	Projection	Projection	

Survey	MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	EW (usft)	Closure Distance (usft)	Closure Azimuth (°)	DLeg (°/100ft)	Northing (usft)	Easting (usft)
RN25- 168H SHL											
	0.00	0.00	0.00	0.00	-650.60	2.80	0.00	0.00	0.00	463,989.50	624,232.80
	157.00	0.40	315.50	157.00	-650.21	2.42	0.55	315.50	0.25	463,989.89	624,232.42
	248.00	0.70	303.70	247.99	-649.67	1.73	1.41	310.89	0.35	463,990.43	624,231.73
	317.00	1.30	317.50	316.98	-648.86	0.85	2.61	311.71	0.93	463,991.24	624,230.85
	370.00	1.10	321.70	369.97	-648.02	0.13	3.71	314.01	0.41	463,992.08	624,230.13
	460.00	1.20	316.60	459.95	-646.66	-1.05	5.51	315.65	0.16	463,993.44	624,228.95
	552.00	1.40	322.10	551.93	-645.07	-2.41	7.59	316.73	0.26	463,995.03	624,227.59
	644.00	1.50	321.70	643.90	-643.24	-3.84	9.91	317.94	0.11	463,996.86	624,226.16
	734.00	1.00	301.80	733.88	-641.90	-5.24	11.85	317.26	0.73	463,998.20	624,224.76
	826.00	0.90	227.20	825.87	-641.97	-6.45	12.65	313.01	1.25	463,998.13	624,223.55
	943.00	1.10	219.00	942.85	-643.47	-7.83	12.80	303.86	0.21	463,996.63	624,222.17
	1,036.00	1.30	216.60	1,034.83	-644.99	-9.01	13.08	295.41	0.22	463,995.11	624,220.99
	1,126.00	1.50	217.90	1,125.80	-646.76	-10.36	13.71	286.27	0.22	463,993.34	624,219.64
	1,216.00	1.70	219.30	1,215.77	-648.72	-11.93	14.85	277.27	0.23	463,991.38	624,218.07
	1,308.00	0.90	216.10	1,307.75	-650.36	-13.22	16.02	270.85	0.87	463,989.74	624,216.78
	1,400.00	0.30	232.00	1,399.74	-651.09	-13.83	16.64	268.30	0.67	463,989.01	624,216.17
	1,491.00	0.70	227.20	1,490.74	-651.62	-14.43	17.26	266.62	0.44	463,988.48	624,215.57
	1,582.00	0.90	221.60	1,581.73	-652.53	-15.31	18.21	263.92	0.24	463,987.57	624,214.89
	1,673.00	1.30	224.40	1,672.71	-653.80	-16.51	19.57	260.58	0.44	463,986.30	624,213.49
	1,763.00	0.70	208.70	1,762.70	-655.01	-17.49	20.76	257.73	0.73	463,985.09	624,212.51

Survey Report Landscape

Company: XTO Energy
 Project: Eddy County, NM (NAD27) NMEZ Grid
 Site: Remuda North 25 State 107H, 127H, 128H, 168H, 908H
 Well: RN25-168H
 Wellbore: 168H Lateral
 Design: 168H Lateral AsDrilled

Local Co-ordinate Reference:
 TVD Reference: 3074+25 @ 3099.00usft (TT1101)
 MD Reference: 3074+25 @ 3099.00usft (TT1101)
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature
 Database: STRYKER_EDM

Survey	MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	EW (usft)	Closure Distance (usft)	Closure Azimuth (°)	D Leg (°/100ft)	Northing (usft)	Easting (usft)
	1,853.00	1.40	217.80	1,852.68	-656.36	-18.42	21.99	254.81	0.80	463,983.74	624,211.58
	1,944.00	1.50	232.10	1,943.65	-657.97	-20.05	24.01	252.11	0.41	463,982.13	624,209.95
	2,035.00	1.00	280.30	2,034.63	-658.56	-21.77	25.82	252.04	1.23	463,981.54	624,208.23
	2,126.00	1.60	359.10	2,125.61	-657.15	-22.57	26.20	255.52	1.88	463,982.95	624,207.43
	2,218.00	1.80	354.30	2,217.58	-654.59	-22.72	25.83	261.11	0.15	463,985.51	624,207.28
	2,309.00	1.80	346.10	2,308.54	-651.94	-23.18	26.02	267.05	0.35	463,988.16	624,206.82
	2,399.00	1.50	345.80	2,398.50	-649.42	-23.81	26.64	272.53	0.33	463,990.68	624,206.19
	2,489.00	1.30	96.80	2,488.49	-648.40	-23.09	25.98	274.85	2.57	463,991.70	624,206.91
	2,580.00	1.70	107.60	2,579.46	-648.93	-20.78	23.64	274.04	0.54	463,991.17	624,209.22
	2,670.00	2.20	114.80	2,669.40	-650.06	-17.94	20.74	271.49	0.62	463,990.04	624,212.06
	2,761.00	2.20	117.70	2,760.34	-651.61	-14.80	17.63	266.73	0.12	463,988.49	624,215.20
	2,851.00	2.70	120.30	2,850.25	-653.48	-11.44	14.53	258.58	0.57	463,986.62	624,218.56
	2,942.00	1.90	130.20	2,941.18	-655.53	-8.44	12.28	246.31	0.98	463,984.57	624,221.56
	3,033.00	1.50	149.60	3,032.14	-657.53	-6.69	11.75	233.83	0.76	463,982.57	624,223.31
	3,124.00	1.70	151.40	3,123.10	-659.75	-5.44	12.31	222.01	0.23	463,980.35	624,224.56
	3,139.00	1.70	151.40	3,138.10	-660.14	-5.22	12.46	220.08	0.00	463,979.96	624,224.78
	3,214.00	1.80	212.70	3,213.07	-662.11	-5.33	14.09	215.24	2.38	463,977.99	624,224.67
	3,304.00	1.80	152.70	3,303.03	-664.55	-5.44	16.21	210.58	2.00	463,975.55	624,224.56
	3,395.00	1.80	150.40	3,393.99	-667.06	-4.08	17.84	202.69	0.08	463,973.04	624,225.92
	3,485.00	1.50	129.60	3,483.95	-669.04	-2.48	19.18	195.97	0.74	463,971.06	624,227.52
	3,576.00	1.40	114.10	3,574.92	-670.26	-0.54	19.94	189.65	0.44	463,969.84	624,229.46
	3,667.00	1.50	107.30	3,665.89	-671.07	1.61	20.50	183.33	0.22	463,969.03	624,231.61
	3,757.00	1.50	111.80	3,755.86	-671.85	3.83	21.28	177.24	0.13	463,968.25	624,233.83
	3,847.00	0.70	114.70	3,845.84	-672.52	5.42	22.08	173.19	0.89	463,967.58	624,235.42
	3,939.00	0.50	103.80	3,937.84	-672.85	6.32	22.53	171.01	0.25	463,967.25	624,236.32
	4,031.00	0.50	111.90	4,029.84	-673.10	7.08	22.90	169.22	0.08	463,967.00	624,237.08
	4,122.00	0.50	105.80	4,120.83	-673.35	7.83	23.30	167.53	0.06	463,966.75	624,237.83

Survey Report Landscape

Company: XTO Energy
Project: Eddy County, NM (NAD27) NMEZ Grid
Site: Remuda North 25 State 107H, 127H, 128H, 168H, 908H
Well: RN25-168H
Wellbore: 168H Lateral
Design: 168H Lateral ASDrilled

Local Co-ordinate Reference: Site Remuda North 25 State 107H, 127H, 128H, 16
TVD Reference: 3074+25 @ 3099.00usft (Ttr101)
MD Reference: 3074+25 @ 3099.00usft (Ttr101)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: STRYKER_EDM

Survey	MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)	D Leg (°/100ft)	Northing (usft)	Easting (usft)
	4,213.00	0.60	107.70	4,211.83	-673.61	8.67	23.74	165.69	0.11	463,966.49	624,238.67
	4,304.00	0.60	116.90	4,302.82	-673.97	9.55	24.32	163.89	0.11	463,966.13	624,239.55
	4,395.00	0.60	111.10	4,393.82	-674.35	10.42	24.94	162.22	0.07	463,965.75	624,240.42
	4,485.00	0.40	108.30	4,483.81	-674.62	11.15	25.43	160.82	0.22	463,965.48	624,241.15
	4,574.00	0.40	84.40	4,572.81	-674.69	11.76	25.70	159.60	0.19	463,965.41	624,241.76
	4,665.00	0.50	96.90	4,663.81	-674.70	12.47	25.97	158.14	0.15	463,965.40	624,242.47
	4,756.00	0.40	109.90	4,754.81	-674.85	13.16	26.37	156.96	0.16	463,965.25	624,243.16
	4,846.00	0.50	100.40	4,844.80	-675.03	13.85	26.81	155.67	0.14	463,965.07	624,243.85
	4,936.00	0.50	113.80	4,934.80	-675.25	14.59	27.33	154.44	0.13	463,964.85	624,244.59
	5,027.00	0.50	123.00	5,025.80	-675.63	15.29	27.97	153.49	0.09	463,964.47	624,245.29
	5,119.00	0.60	121.80	5,117.79	-676.10	16.03	28.73	152.58	0.11	463,964.00	624,246.03
	5,211.00	0.70	112.60	5,209.79	-676.57	16.96	29.58	151.40	0.16	463,963.53	624,246.96
	5,302.00	0.70	107.90	5,300.78	-676.96	18.00	30.43	150.02	0.06	463,963.14	624,248.00
	5,393.00	0.80	113.40	5,391.77	-677.38	19.12	31.36	148.65	0.14	463,962.72	624,249.12
	5,483.00	0.70	116.50	5,481.77	-677.88	20.18	32.34	147.49	0.12	463,962.22	624,250.18
	5,575.00	0.60	123.80	5,573.76	-678.39	21.09	33.27	146.66	0.14	463,961.71	624,251.09
	5,665.00	0.40	138.30	5,663.76	-678.89	21.69	34.02	146.27	0.26	463,961.21	624,251.69
	5,756.00	0.80	105.70	5,754.75	-679.30	22.51	34.82	145.52	0.56	463,960.80	624,252.51
	5,846.00	0.90	100.90	5,846.74	-679.61	23.84	35.84	144.05	0.13	463,960.49	624,253.84
	5,936.00	1.00	96.70	5,936.73	-679.84	25.31	36.90	142.40	0.14	463,960.26	624,255.31
	6,029.00	0.80	96.80	6,027.72	-680.00	26.73	37.91	140.86	0.22	463,960.10	624,256.73
	6,120.00	0.90	106.40	6,118.71	-680.28	28.05	38.97	139.61	0.19	463,959.82	624,258.05
	6,208.00	0.90	111.10	6,206.70	-680.72	29.36	40.16	138.60	0.08	463,959.38	624,259.36
	6,298.00	0.90	111.80	6,296.69	-681.24	30.67	41.42	137.71	0.01	463,958.86	624,260.67
	6,390.00	1.00	117.50	6,388.67	-681.88	32.06	42.83	136.92	0.15	463,958.22	624,262.06
	6,481.00	1.00	126.30	6,479.66	-682.72	33.40	44.36	136.39	0.17	463,957.38	624,263.40
	6,571.00	1.10	132.10	6,569.64	-683.76	34.67	46.00	136.13	0.16	463,956.34	624,264.67

Survey Report Landscape

Company: XTO Energy
Project: Eddy County, NM (NAD27) NMEZ Grid
Site: Remuda North 25 State 107H, 127H, 128H, 168H, 908H
Well: RN25-168H
Wellbore: 168H Lateral
Design: 168H Lateral AsDrilled

Local Co-ordinate Reference:
TVD Reference: 3074+25 @ 3099.00usft (TT1101)
MD Reference: 3074+25 @ 3099.00usft (TT1101)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: STRYKER_EDM

Survey	MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	NIS (usft)	EW (usft)	Closure Distance (usft)	Closure Azimuth (°)	D Leg (°/100ft)	Northing (usft)	Easting (usft)
	6,663.00	1.10	133.90	6,661.63	-684.97	35.96	47.76	136.02	0.04	463,965.13	624,266.96
	6,755.00	1.20	137.10	6,753.61	-686.28	37.26	49.60	136.00	0.13	463,963.82	624,267.26
	6,846.00	1.10	142.60	6,844.59	-687.68	38.44	51.43	136.13	0.16	463,962.42	624,268.44
	6,936.00	1.30	145.80	6,934.57	-689.21	39.53	53.29	136.42	0.23	463,960.89	624,269.53
	7,027.00	1.50	140.70	7,025.54	-690.98	40.87	55.50	136.69	0.26	463,949.12	624,270.87
	7,120.00	1.50	138.50	7,118.51	-692.84	42.45	57.93	136.81	0.06	463,947.26	624,272.45
	7,210.00	1.70	143.20	7,208.48	-694.79	44.03	60.43	136.98	0.27	463,945.31	624,274.03
	7,302.00	1.70	142.40	7,300.44	-696.96	45.68	63.15	137.24	0.03	463,943.14	624,275.68
	7,392.00	1.50	132.10	7,390.40	-698.81	47.37	65.65	137.25	0.39	463,941.29	624,277.37
	7,481.00	1.80	125.00	7,479.36	-700.39	49.37	68.18	136.91	0.41	463,939.71	624,279.37
	7,573.00	2.20	119.90	7,571.31	-702.10	52.09	71.29	136.26	0.48	463,938.00	624,282.09
	7,666.00	1.30	119.10	7,664.26	-703.50	54.56	74.01	135.63	0.97	463,936.60	624,284.56
	7,755.00	0.30	229.80	7,753.26	-704.14	55.26	74.96	135.58	1.61	463,935.96	624,286.26
	7,846.00	1.50	270.10	7,844.24	-704.30	53.89	74.12	136.42	1.41	463,935.80	624,283.89
	7,937.00	2.10	276.10	7,935.20	-704.12	51.04	72.05	137.97	0.69	463,935.98	624,281.04
	8,028.00	1.90	260.80	8,026.14	-704.18	47.89	70.03	139.92	0.62	463,935.92	624,277.89
	8,118.00	1.70	235.00	8,116.10	-705.18	45.33	69.20	142.08	0.92	463,934.92	624,275.33
	8,210.00	1.40	215.50	8,208.07	-706.86	43.56	69.49	144.09	0.65	463,933.22	624,273.56
	8,291.00	0.90	183.10	8,289.05	-708.32	42.95	70.31	145.18	0.99	463,931.78	624,272.95
	8,380.00	1.30	104.80	8,378.04	-709.28	43.89	71.63	145.00	1.60	463,930.82	624,273.89
	8,470.00	1.70	110.00	8,468.01	-710.00	46.13	73.52	143.89	0.47	463,930.10	624,275.13
	8,562.00	1.40	127.20	8,559.97	-711.14	48.31	75.74	143.07	0.60	463,928.96	624,276.31
	8,654.00	1.40	142.70	8,651.95	-712.72	49.88	77.94	142.84	0.41	463,927.38	624,279.88
	8,743.00	1.70	133.20	8,740.91	-714.49	51.50	80.33	142.68	0.44	463,925.61	624,281.50
	8,835.00	2.00	91.10	8,832.87	-715.45	54.10	82.69	141.65	1.48	463,924.65	624,284.10
	8,925.00	3.00	105.80	8,922.79	-716.12	57.94	85.64	139.92	1.31	463,923.98	624,287.94
	9,016.00	1.90	109.70	9,013.70	-717.28	61.65	88.94	138.57	1.22	463,922.82	624,291.65

Survey Report Landscape

Company: XTO Energy
Project: Eddy County, NM (NAD27) NMEZ Grid
Site: Remuda North 25 State 107H, 127H, 128H, 168H, 908H
Well: RN25-168H
Wellbore: 168H Lateral
Design: 168H Lateral AsDrilled

Local Co-ordinate Reference:
TVD Reference: 3074+25 @ 3099.00usft (TT101)
MD Reference: 3074+25 @ 3099.00usft (TT101)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: STRYKER_EDM

Survey	MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)	D Leg (°/100ft)	Northing (usft)	Easting (usft)
	9,106.00	1.40	104.20	9,103.66	-718.05	64.12	91.16	137.73	0.58	463,922.05	624,294.12
	9,198.00	1.60	111.90	9,195.63	-718.81	66.40	93.26	137.00	0.31	463,921.29	624,296.40
	9,288.00	1.30	89.40	9,285.60	-719.26	68.59	95.09	136.22	0.71	463,920.84	624,298.59
	9,379.00	1.50	78.50	9,376.58	-719.02	70.79	96.45	135.18	0.37	463,921.08	624,300.79
	9,469.00	1.90	78.40	9,466.54	-718.48	73.40	97.94	133.87	0.44	463,921.62	624,303.40
	9,561.00	1.30	64.80	9,558.50	-717.73	75.84	99.21	132.58	0.77	463,922.37	624,305.84
	9,661.00	1.00	75.50	9,648.48	-717.10	77.53	100.03	131.67	0.41	463,923.00	624,307.53
	9,742.00	1.10	96.70	9,739.47	-717.00	79.16	101.20	131.01	0.44	463,923.10	624,309.16
	9,833.00	1.00	100.70	9,830.45	-717.25	80.81	102.61	130.51	0.14	463,922.85	624,310.81
	9,923.00	0.90	116.30	9,920.44	-717.71	82.22	103.97	130.20	0.31	463,922.39	624,312.22
	10,014.00	0.70	136.60	10,011.43	-718.43	83.24	105.22	130.14	0.38	463,921.67	624,313.24
	10,104.00	0.40	152.90	10,101.43	-719.11	83.76	106.06	130.24	0.37	463,920.99	624,313.76
	10,195.00	0.90	106.80	10,192.42	-719.60	84.59	107.01	130.15	0.75	463,920.50	624,314.59
	10,285.00	1.40	107.90	10,282.40	-720.14	86.31	108.67	129.78	0.56	463,919.96	624,316.31
	10,381.00	1.40	112.50	10,378.37	-720.95	88.51	110.89	129.38	0.12	463,919.15	624,318.51
	10,435.00	1.80	120.10	10,432.35	-721.63	89.85	112.35	129.21	0.84	463,918.47	624,319.85
	10,496.00	1.90	123.63	10,493.32	-722.67	91.53	114.31	129.09	0.25	463,917.43	624,321.53
	10,566.00	1.56	132.02	10,563.28	-724.31	93.68	117.02	129.05	0.47	463,915.79	624,323.68
	10,677.00	1.90	137.00	10,674.24	-726.25	95.63	119.75	129.18	0.41	463,913.85	624,325.63
	10,722.00	1.07	149.73	10,719.23	-726.40	96.28	120.35	129.04	5.72	463,913.70	624,326.28
	10,768.00	6.46	352.55	10,765.12	-723.42	96.09	118.35	127.98	12.02	463,916.68	624,326.09
	10,813.00	11.30	352.65	10,809.56	-716.54	95.19	113.51	125.51	10.76	463,923.56	624,325.19
	10,858.00	16.03	352.38	10,853.28	-706.00	93.81	106.54	121.33	10.51	463,934.10	624,323.81
	10,904.00	20.25	354.63	10,896.98	-691.77	92.22	98.44	114.72	9.30	463,948.33	624,322.22
	10,949.00	23.10	356.66	10,938.80	-675.20	91.00	91.57	105.59	6.59	463,964.90	624,321.00
	10,994.00	26.73	355.84	10,979.60	-656.29	89.79	87.17	93.74	8.12	463,983.81	624,319.79
	11,040.00	28.15	355.12	11,020.43	-635.16	88.11	86.70	79.74	3.17	464,004.94	624,318.11

Survey Report Landscape

Company: XTO Energy
Project: Eddy County, NM (NAD27) NMEZ Grid
Site: Remuda North 25 State 107H, 127H, 128H, 168H, 908H
Well: RN25-168H
Wellbore: 168H Lateral
Design: 168H Lateral AsDrilled

Local Co-ordinate Reference: Site Remuda North 25 State 107H, 127H, 128H, 16
TVD Reference: 3074+25 @ 3099.00usft (Ttr101)
MD Reference: 3074+25 @ 3099.00usft (Ttr101)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: STRYKER_EDM

Survey	MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	NS (usft)	EW (usft)	Closure Distance (usft)	Closure Azimuth (°)	DLeg (°/100ft)	Northing (usft)	Easting (usft)
	11,066.00	33.04	353.76	11,060.01	-611.87	85.83	91.62	64.99	10.74	464,028.23	624,315.83
	11,131.00	37.03	355.56	11,096.85	-586.15	83.45	103.24	51.37	9.16	464,053.95	624,313.45
	11,221.00	44.05	355.14	11,165.20	-527.88	78.70	144.29	31.74	7.81	464,112.22	624,308.70
	11,312.00	52.49	353.41	11,225.72	-460.38	71.87	202.37	19.96	9.38	464,179.72	624,301.87
	11,403.00	60.96	352.27	11,275.61	-384.97	62.36	272.23	12.64	9.37	464,255.13	624,292.36
	11,405.00	61.11	352.28	11,276.57	-383.23	62.12	273.87	12.51	7.64	464,256.87	624,292.12
Wellpath Crosses Unit Line @ Heel											
	11,493.00	67.82	352.72	11,314.48	-304.55	51.77	349.50	8.05	7.64	464,335.55	624,281.77
	11,585.00	77.13	354.52	11,342.16	-217.46	42.07	434.91	5.18	10.29	464,422.64	624,272.07
	11,656.62	81.57	356.09	11,355.95	-144.40	36.08	507.30	3.76	6.29	464,495.70	624,266.08
RN25- 168H LP											
	11,674.00	82.42	356.39	11,357.95	-130.19	35.14	521.42	3.56	6.29	464,509.91	624,265.14
Wellpath Crosses FTP 251FSL											
	11,674.37	82.44	356.40	11,356.00	-129.82	35.12	521.79	3.55	6.29	464,510.28	624,265.12
RN25- 168H FTP_251FSL_614FWL											
	11,676.00	82.54	356.43	11,356.21	-128.21	35.02	523.39	3.53	6.29	464,511.89	624,265.02
	11,753.00	88.55	1.62	11,364.20	-51.51	33.73	599.89	2.96	10.30	464,588.59	624,263.73
Wellpath Crosses 330' HL @ Heel											
	11,764.00	89.41	2.36	11,364.39	-40.52	34.11	610.88	2.94	10.30	464,599.58	624,264.11
	11,856.00	89.94	2.51	11,364.92	51.39	38.02	702.86	2.87	0.60	464,691.49	624,268.02
	11,947.00	88.99	1.24	11,365.76	142.34	41.00	793.86	2.76	1.74	464,782.44	624,271.00
	12,036.00	90.34	0.55	11,366.30	233.32	42.42	884.81	2.57	1.67	464,873.42	624,272.42
	12,127.00	89.86	2.18	11,366.14	322.30	44.54	973.79	2.46	1.91	464,962.40	624,274.54
	12,219.00	91.76	7.52	11,364.84	413.92	52.31	1,065.67	2.66	6.16	465,054.02	624,282.31
	12,308.00	89.80	5.96	11,363.63	502.29	62.76	1,154.45	2.98	2.81	465,142.39	624,292.76
	12,399.00	88.04	0.14	11,365.35	593.10	67.60	1,245.39	2.98	6.68	465,233.20	624,297.60
	12,489.00	89.94	2.50	11,366.93	683.05	69.67	1,335.33	2.87	3.37	465,323.15	624,299.67
	12,580.00	91.12	357.30	11,366.09	774.02	69.51	1,426.18	2.68	5.86	465,414.12	624,299.51

Survey Report Landscape

Company: XTO Energy
Project: Eddy County, NM (NAD27) NMEZ Grid
Site: Remuda North 25 State 107H, 127H, 128H, 168H, 908H
Well: RN25-168H
Wellbore: 168H Lateral
Design: 168H Lateral AsDrilled

Local Co-ordinate Reference: Site Remuda North 25 State 107H, 127H, 128H, 16
TVD Reference: 3074+25 @ 3099.00usft (Ttr101)
MD Reference: 3074+25 @ 3099.00usft (Ttr101)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: STRYKER_EDM

Survey	MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)	D Leg (°/100ft)	Northing (usft)	Easting (usft)
	12,671.00	90.59	356.28	11,364.73	864.86	64.42	1,516.71	2.33	1.26	465,504.96	624,294.42
	12,760.00	89.24	354.76	11,364.86	953.58	57.46	1,605.12	1.95	2.28	465,593.68	624,287.46
	12,850.00	89.97	358.77	11,365.48	1,043.42	52.39	1,694.75	1.68	4.53	465,683.52	624,282.39
	12,953.00	90.06	357.99	11,365.46	1,146.38	49.47	1,797.58	1.49	0.76	465,786.48	624,279.47
	13,042.00	90.00	358.14	11,365.41	1,235.33	46.47	1,886.43	1.33	0.18	465,875.43	624,276.47
	13,132.00	90.00	356.74	11,365.41	1,325.24	42.45	1,976.23	1.15	1.56	465,965.34	624,272.45
	13,223.00	89.41	357.65	11,365.88	1,416.12	38.00	2,067.02	0.98	1.19	466,056.22	624,268.00
	13,314.00	89.19	358.22	11,366.99	1,507.06	34.72	2,157.89	0.85	0.67	466,147.16	624,264.72
	13,405.00	87.23	357.00	11,369.83	1,597.93	30.93	2,248.70	0.72	2.54	466,238.03	624,260.93
	13,495.00	92.04	359.49	11,370.41	1,687.85	28.17	2,338.59	0.62	6.02	466,327.95	624,258.17
	13,587.00	92.41	359.31	11,366.83	1,779.78	27.21	2,430.50	0.58	0.45	466,419.88	624,257.21
	13,678.00	91.88	359.61	11,363.43	1,870.71	26.35	2,521.42	0.54	0.67	466,510.81	624,256.35
	13,768.00	89.27	359.65	11,362.53	1,960.69	25.77	2,611.39	0.50	2.90	466,600.79	624,255.77
	13,860.00	91.09	1.18	11,362.24	2,052.68	26.44	2,703.39	0.50	2.58	466,692.78	624,256.44
	13,950.00	88.91	1.18	11,362.24	2,142.66	28.29	2,793.38	0.52	2.42	466,782.76	624,258.29
	14,042.00	88.96	0.65	11,363.95	2,234.63	29.92	2,885.36	0.54	0.36	466,874.73	624,259.92
	14,133.00	87.76	1.04	11,366.55	2,325.58	31.42	2,976.32	0.55	1.34	466,965.68	624,261.42
	14,224.00	90.64	0.82	11,367.82	2,416.55	32.90	3,067.29	0.56	3.17	467,056.65	624,262.90
	14,315.00	91.32	0.89	11,366.26	2,507.52	34.25	3,158.28	0.57	0.75	467,147.62	624,264.25
	14,405.00	91.96	0.71	11,363.69	2,597.48	35.51	3,248.24	0.58	0.74	467,237.58	624,265.51
	14,496.00	88.99	358.89	11,362.93	2,688.46	35.19	3,339.22	0.56	3.83	467,328.56	624,265.19
	14,586.00	91.15	359.63	11,362.82	2,778.45	34.03	3,429.19	0.52	2.54	467,418.55	624,264.03
	14,676.00	92.24	0.36	11,360.16	2,868.40	34.02	3,519.14	0.51	1.46	467,508.50	624,264.02
	14,767.00	91.60	0.52	11,357.11	2,959.35	34.72	3,610.09	0.51	0.72	467,599.45	624,264.72
	14,859.00	91.48	1.39	11,354.64	3,051.30	36.25	3,702.05	0.52	0.95	467,691.40	624,266.25
	14,949.00	92.10	1.38	11,351.83	3,141.23	38.43	3,792.00	0.54	0.69	467,781.33	624,268.43
	15,040.00	90.03	359.01	11,350.14	3,232.20	38.74	3,882.97	0.53	3.46	467,872.30	624,268.74

Survey Report Landscape

Company: XTO Energy
Project: Eddy County, NM (NAD27) NMEZ Grid
Site: Remuda North 25 State 107H, 127H, 128H, 168H, 908H
Well: RN25-168H
Wellbore: 168H Lateral
Design: 168H Lateral AsDrilled

Local Co-ordinate Reference:
TVD Reference: Site Remuda North 25 State 107H, 127H, 128H, 16
MD Reference: 3074+25 @ 3099.00usft (Tm101)
North Reference: 3074+25 @ 3099.00usft (Tm101)
Survey Calculation Method: Grid
Database: Minimum Curvature
 STRYKER_EDM

Survey	MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	NIS (usft)	EW (usft)	Closure Distance (usft)	Closure Azimuth (°)	DLeg (°/100ft)	Northing (usft)	Easting (usft)
	15,131.00	91.88	358.85	11,348.62	3,323.17	37.04	3,973.92	0.49	2.04	467,963.27	624,267.04
	15,223.00	91.79	357.98	11,345.68	3,415.09	34.49	4,065.81	0.45	0.95	468,055.19	624,264.49
	15,314.00	89.78	357.74	11,344.43	3,506.01	31.10	4,156.71	0.39	2.22	468,146.11	624,261.10
	15,404.00	89.19	357.74	11,345.24	3,595.94	27.55	4,246.61	0.33	0.66	468,236.04	624,257.55
	15,494.00	88.66	357.55	11,346.93	3,685.85	23.85	4,336.50	0.28	0.63	468,325.95	624,253.85
	15,585.00	89.86	357.87	11,348.10	3,776.76	20.21	4,427.40	0.23	1.36	468,416.86	624,250.21
	15,674.00	90.00	358.46	11,348.21	3,865.72	17.36	4,516.34	0.18	0.68	468,505.82	624,247.36
	15,764.00	90.48	358.83	11,347.83	3,955.69	15.24	4,606.31	0.15	0.67	468,595.79	624,245.24
	15,856.00	90.95	359.13	11,346.69	4,047.67	13.60	4,698.28	0.13	0.61	468,687.77	624,243.60
	15,948.00	90.92	359.17	11,345.18	4,139.65	12.23	4,790.26	0.11	0.05	468,779.75	624,242.23
	16,039.00	91.09	359.60	11,343.59	4,230.63	11.26	4,881.24	0.10	0.51	468,870.73	624,241.26
	16,131.00	91.37	359.48	11,341.61	4,322.60	10.52	4,973.21	0.09	0.33	468,962.70	624,240.52
	16,223.00	91.71	359.56	11,339.14	4,414.57	9.75	5,065.17	0.08	0.38	469,054.67	624,239.75
	16,314.00	91.23	359.55	11,336.81	4,505.53	9.04	5,156.14	0.07	0.53	469,145.63	624,239.04
	16,404.00	90.98	359.46	11,335.07	4,595.51	8.26	5,246.12	0.06	0.30	469,235.61	624,238.26
	16,495.00	90.62	359.38	11,333.80	4,686.50	7.34	5,337.10	0.05	0.41	469,326.60	624,237.34
	16,586.00	90.87	359.24	11,332.62	4,777.49	6.25	5,428.09	0.04	0.31	469,417.59	624,236.25
	16,676.00	89.55	359.97	11,332.29	4,867.48	5.63	5,518.08	0.03	1.68	469,507.58	624,235.63
	16,768.00	89.58	359.77	11,332.99	4,959.48	5.42	5,610.08	0.03	0.22	469,599.58	624,235.42
	16,858.00	90.11	359.98	11,333.23	5,049.48	5.22	5,700.08	0.02	0.63	469,689.58	624,235.22
	16,948.00	90.39	0.33	11,332.84	5,139.48	5.47	5,790.08	0.03	0.50	469,779.58	624,235.47
	17,038.00	91.32	0.22	11,331.49	5,229.46	5.90	5,880.06	0.03	1.04	469,869.56	624,235.90
	17,129.00	91.29	0.01	11,329.42	5,320.44	6.08	5,971.04	0.03	0.23	469,960.54	624,236.08
	17,221.00	90.78	0.03	11,327.76	5,412.42	6.11	6,063.02	0.03	0.55	470,052.52	624,236.11
	17,312.00	90.00	359.89	11,327.14	5,503.42	6.05	6,154.02	0.03	0.87	470,143.52	624,236.05
	17,403.00	89.80	359.52	11,327.30	5,594.42	5.58	6,245.02	0.03	0.46	470,234.52	624,235.58
	17,495.00	89.58	0.63	11,327.80	5,686.42	5.70	6,337.02	0.03	1.23	470,326.52	624,235.70

Survey Report Landscape

Company: XTO Energy
 Project: Eddy County, NM (NAD27) NMEZ Grid
 Site: Remuda North 25 State 107H, 127H, 128H, 168H, 908H
 Well: RN25-168H
 Wellbore: 168H Lateral
 Design: 168H Lateral AsDrilled

Local Co-ordinate Reference:
 TVD Reference: 3074+25 @ 3089.00usft (Ttr101)
 MD Reference: 3074+25 @ 3089.00usft (Ttr101)
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature
 Database: STRYKER_EDM

Survey	MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	NIS (usft)	EW (usft)	Closure Distance (usft)	Closure Azimuth (°)	D-Leg (°/100ft)	Northing (usft)	Easting (usft)
	17,567.00	89.22	0.24	11,328.76	5,778.41	6.40	6,429.01	0.03	0.58	470,418.51	624,236.40
	17,678.00	89.08	359.34	11,330.11	5,869.40	6.06	6,520.00	0.03	1.00	470,509.50	624,236.06
	17,769.00	91.79	359.17	11,329.42	5,960.38	4.88	6,610.98	0.02	2.98	470,600.48	624,234.88
	17,860.00	91.54	358.78	11,326.77	6,051.32	3.25	6,701.92	0.00	0.51	470,691.42	624,233.25
	17,950.00	91.34	358.96	11,324.51	6,141.28	1.48	6,791.88	359.99	0.30	470,781.38	624,231.48
	18,041.00	91.15	358.86	11,322.54	6,232.24	-0.25	6,882.84	359.97	0.24	470,872.34	624,229.75
	18,132.00	90.90	358.42	11,320.91	6,323.20	-2.41	6,973.80	359.96	0.56	470,963.30	624,227.59
	18,223.00	91.06	358.40	11,319.35	6,414.15	-4.93	7,064.76	359.94	0.18	471,054.25	624,225.07
	18,314.00	90.34	357.12	11,318.24	6,505.07	-8.49	7,155.68	359.91	1.61	471,145.17	624,221.51
	18,403.00	90.00	359.19	11,317.98	6,594.02	-11.36	7,244.64	359.89	2.36	471,234.12	624,218.64
	18,494.00	89.22	358.18	11,318.60	6,684.99	-13.44	7,335.61	359.87	1.40	471,325.09	624,216.56
	18,585.00	89.38	359.78	11,319.71	6,775.97	-15.06	7,426.59	359.86	1.77	471,416.07	624,214.94
	18,676.00	90.39	359.35	11,319.89	6,866.97	-15.75	7,517.59	359.86	1.21	471,507.07	624,214.25
	18,766.00	89.92	1.38	11,319.65	6,956.96	-15.18	7,607.58	359.86	2.32	471,597.06	624,214.82
	18,857.00	90.22	2.34	11,319.54	7,047.91	-12.23	7,698.52	359.89	1.11	471,688.01	624,217.77
	18,948.00	91.04	3.34	11,318.53	7,138.79	-7.72	7,789.40	359.92	1.42	471,778.89	624,222.28
	19,039.00	90.53	2.97	11,317.29	7,229.64	-2.71	7,880.24	359.96	0.69	471,869.74	624,227.29
	19,066.20	89.90	2.11	11,317.19	7,266.82	-1.51	7,907.42	359.97	3.92	471,896.92	624,228.49
	RN25- 168H LTP _330FNL_660FEL										
	19,067.00	89.88	2.09	11,317.19	7,267.62	-1.48	7,908.22	359.97	3.92	471,897.72	624,228.52
	Wellpath Crosses LTP 330FNL										
	19,122.00	88.60	0.35	11,317.92	7,312.59	-0.31	7,963.20	359.98	3.92	471,962.69	624,229.69
	19,173.00	88.60	0.35	11,319.16	7,363.58	0.00	8,014.18	359.98	0.00	472,003.68	624,230.00
	TD @ 223FNL_667FEL - RN25- 168H PBHL_200FNL_660FEL										

Survey Report Landscape

Company: XTO Energy
Project: Eddy County, NM (NAD27) NMEZ Grid
Site: Remuda North 25 State 107H, 127H, 128H, 168H, 908H
Well: RN25-168H
Wellbore: 168H Lateral
Design: 168H Lateral AsDrilled

Local Co-ordinate Reference:
 TVD Reference: 3074+25 @ 3099.00usft (Tri101)
 MD Reference: 3074+25 @ 3099.00usft (Tri101)
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature
 Database: STRYKER_EDM

Design Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Comment
11,405.00	11,276.57	-383.23	62.12	Wellpath Crosses Unit Line @ Heel
11,674.00	11,357.95	-130.19	35.14	Wellpath Crosses FTP 251'FSL
11,753.00	11,364.20	-51.51	33.73	Wellpath Crosses 330' HL @ Heel
19,067.00	11,317.19	7,257.62	-1.48	Wellpath Crosses LTP 330'FNL
19,173.00	11,319.16	7,363.58	0.00	TD @ 223'FNL, 657'FEL

Checked By: _____ Approved By: _____ Date: _____