Submit 1 Copy To Appropriate District Office	State of New Me	xico NMC	OCD - REC'D 11/16/202	
<u>District I</u> – (575) 393-6161	Energy, Minerals and Natu	ral Resources		evised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283			VELL API NO. 30-015-47278	
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION		5. Indicate Type of Lease	
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.		STATE FEE X	
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87	6	. State Oil & Gas Lease	No.
87505 SUNDRY NO	TICES AND REPORTS ON WELLS	7	. Lease Name or Unit A	greement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			BEAGLE 35-34-22-27 FEE	
1. Type of Well: Oil Well Gas Well Other			8. Well Number 402H	
2. Name of Operator WPX ENERGY PERMIAN, LLC			9. OGRID Number 246289	
3. Address of Operator			10. Pool name or Wildcat	
3500 ONE WILLIAMS CENTER, MD: 35, TULSA, OK 74172			PURPLE SAGE, WOLFCAMP (GAS)	
4. Well Location	. 1076 feet from the SOUTH	line and 638	C + C + 1	EAST line
Omit Ectici	icet from the	inic and	feet from the IMPM Count	
Section 35	11. Elevation (Show whether DR,		IMPM Count	y EDDY
	3112 RKB	nab, ni, on, e.e.,		
				_
12. Check	Appropriate Box to Indicate N	ature of Notice, Re	port or Other Data	
NOTICE OF	NTENTION TO:	SURSE	QUENT REPORT	OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING				
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A				
	MULTIPLE COMPL	CASING/CEMENT JO	OB 🗌	
DOWNHOLE COMMINGLE				
CLOSED-LOOP SYSTEM [OTHER:	J	OTHER: SPUD AND S	URFACE CASING/CEMENT JOE	3 [X]
13. Describe proposed or con	npleted operations. (Clearly state all p	pertinent details, and gi	ve pertinent dates, inclu-	ding estimated date
	work). SEE RULE 19.15.7.14 NMAC	C. For Multiple Compl	etions: Attach wellbore	diagram of
proposed completion or r	1			
WELL SPUDDED ON 09/05/2020 AND T	HE SURFACE CASING/CEMENT JOB DETAILS AR	E AS FOLLOWS:		
	1' MD; DEPTH OF 13 3/8" SURFACE CASING = 4	15'		
CASING WEIGHT = 54.5#, GRADE = J-55 RAN 09/05/2020 5 CENTRALIZERS USED; SETTING DEPTH OF SHOE = 415'				
403 SX 14.8 PPG TAIL CLASS C; TOP OF CEMENT = SURFACE				
27 BBLS TO SURFACE (NO LOSSES); CAS	ING TEST = 1500 FOR 30 MINUTES			
PLEASE ACCEPT MY APOLOGIES FOR TH	HE DELAYED REPORTING DUE TO ISSUES WITH	THE ONLINE SYSTEM.		
Spud Date: 11/09/2020	Rig Release Da	te·		
39ud Bate. 11/03/2020				
I hereby certify that the information	n above is true and complete to the bo	est of my knowledge ar	nd belief.	
	1/.			
SIGNATURE	Nene TITLE RE	GULATORY TECH II	DATE	11/16/2020
Type or print name LORRI KLINE	E-mail address	: LORRI.KLINE@WPXENE	ERGY.COM PHONE:	539-573-3518
For State Use Only				
100				
APPROVED BY:	TITLE	Staff Mana	ger DATE 1	1/25/2020