REGEIVED FEB 1,6 2012

UNITED STATES OCD-ARTESIA

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED OM B No 1004-0137 Expires: March 31, 2007

5	Lease Serial	No.

SUNDRY	INCLICES WIND UP	4- 4-11 4	antar an	6. If Indian, A	Allottee or Tribe Name		
DARIES And use th	is form for proposals ell. Use Form 3160 - 3	to ariii or to re- (APD) for such ni	ronoeale	1			
abandoned we	en. Ose Form 3160-3	(APD) for such pr	oposais.				
SUBMIT IN TRI	IPLICATE - Other ins	structions on reve	rse side.		CA/Agreement, Name ar		
1. Type of Well ✓ Oil Well Gas Well Other					Poker Lake Unit NMNM 71016X		
2. Name of Operator BOPCO, L. F				8 Well Name and No. Poker Lake Unit 344H			
		Las as as a second		9. API Well 30-015-3		•	
3a. Address P. O. Box 2760 Midland, TX 7	79702	3b. Phone No. (included) 432-683-2277	de area code)		Pool, or Exploratory Are		
4. Location of Well (Footage, Sec.,	T., R., M., or Survey Description)		Poker La	ke NW (Delaware)		
SHL: SESW, UL N, 35' FSL, 1 BHL: 115' FNL, 2215' FWL, S				1	Parish, State unty, NM		
12. CHECK AF	PROPRIATE BOX(ES) T	O INDICATE NATU	RE OF NOTICE,	REPORT, OR	OTHER DATA		
TYPE OF SUBMISSION	Maria de la companya del companya de la companya de la companya del companya de la companya de l	TY	PE OF ACTION			_	
✓ Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production Reclamation	(Start/Resume)	Water Shut-Off Well Integrity		
Subsequent Report	Casing Repair	New Construction	Recomplete		Other Alter Ceme	nt	
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	Temporarily Water Dispo				
Attach the Bond under which the following completion of the investing has been completed. Fir determined that the site is ready	ctionally or recomplete horizont ne work will be performed or pro- volved operations. If the operational Abandonment Notices shall be	rtinent details, including es ally, give subsurface locati ovide the Bond No. on file on results in a multiple com- be filed only after all requir	timated starting date ons and measured and with BLM/BIA. Recupletion or recompletic ements, including rec	of any proposed work d true vertical depths quired subsequent rep on in a new interval, lamation, have been	of all pertinent markers orts shall be filed within a Form 3160-4 shall be	and 30 file	
If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Fit determined that the site is ready BOPCO, L.P. respectfully Given the PLU #344H is of job, to a one stage cement for a DV tool. Computer a success at circulating cemet cement for 18 hrs or until	ctionally or recomplete horizonthe work will be performed or provolved operations. If the operational Abandonment Notices shall be for final inspection.)	rtinent details, including es ally, give subsurface location of the Bond No. on file on results in a multiple combe filed only after all requirable to the Bond No. on file on results in a multiple combe filed only after all requirable to the approved for the T'', 26 ppf, N-80, LTC casing should be company, based of the theory of the the	timated starting date of one and measured and with BLM/BIA. Recupletion or recompletic ements, including record the above caption as a BOPCO, L.P. record casing which will be set ichever time is greeichever time is greeich on some and the starting which will be set ichever time is greeich and measurements.	of any proposed work of true vertical depths quired subsequent repon in a new interval, lamation, have been depended well. equests to change be set at 8,101' M by BOPCO, L.P., stat 3,953'. BOPC ater. TOC will be	of all pertinent markers outs shall be filed within a Form 3160-4 shall be completed, and the operation of the planned two stag D. This will negate to suggests a high probact of L.P. shall wait on confirmed with a termination of the planned with a termination of the probact of the planned two stages.	and 30 file ato he ibi	
If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Fir determined that the site is ready BOPCO, L.P. respectfully Given the PLU #344H is on job, to a one stage cement for a DV tool. Computer a success at circulating cement cement for 18 hrs or until survey after completion of Spacer: 20 bbl of fresh wat Flush: 80 bbl of fresh wat Lead: 365 sks Tuned Ligh	ctionally or recomplete horizonthe work will be performed or provolved operations. If the operational Abandonment Notices shall be for final inspection.) requests the changes listed butside of both the Secretary job, for the 2nd intermediate modeling provided by the cent 500' into the 9-5/8", 40 pp 500 psi compressive strengticement job. Updated cementer with red dye er at Cement + 0.75 lb/sk CFR-15.6 ppg, 1.19 cu ft/sk, 5.39	rtinent details, including es ally, give subsurface location of the Bond No. on file on results in a multiple combe filed only after all requirible below to be approved for and R-111 Potash are ter 7", 26 ppf, N-80, LTC ement company, based of J55, LTC casing she has been reached, when the volumes are based of the state of the	timated starting date of cons and measured and with BLM/BIA. Recupletion or recompletic ements, including record the above caption ea, BOPCO, L.P. recording which will be in input provided low which will be set ichever time is green 50% excess of gar	of any proposed work of true vertical depths quired subsequent repon in a new interval, lamation, have been demanded by the set at 8,101' Mby BOPCO, L.F., stat 3,953'. BOPCO ater. TOC will be luge hole volume a	of all pertinent markers outs shall be filed within a Form 3160-4 shall be completed, and the operation of the planned two stag D. This will negate to suggests a high probact, L.P. shall wait on confirmed with a tend are listed below:	and 3(file ato he ibi	
If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Fir determined that the site is ready BOPCO, L.P. respectfully Given the PLU #344H is on job, to a one stage cement for a DV tool. Computer a success at circulating cement cement for 18 hrs or until survey after completion of Spacer: 20 bbl of fresh wat Flush: 80 bbl of fresh wat Lead: 365 sks Tuned Ligh	ctionally or recomplete horizonthe work will be performed or provolved operations. If the operational Abandonment Notices shall be for final inspection.) requests the changes listed butside of both the Secretary job, for the 2nd intermediate modeling provided by the cent 500' into the 9-5/8", 40 pp 500 psi compressive strengticement job. Updated cementer with red dye er at Cement + 0.75 lb/sk CFR-15.6 ppg, 1.19 cu ft/sk, 5.39 pice	rtinent details, including es ally, give subsurface location of the Bond No. on file on results in a multiple combe filed only after all require below to be approved for sand R-111 Potash are te 7", 26 ppf, N-80, LTC ment company, based of J. J-55, LTC casing she has been reached, when two lumes are based of the same te are based of the same terms of the	timated starting date of ons and measured and with BLM/BIA. Recupletion or recompletic ements, including record the above caption ea, BOPCO, L.P. recording which will be input provided by which will be set ichever time is green 50% excess of gas bl/sk Poly-E-Flak	of any proposed work of true vertical depths quired subsequent repon in a new interval, lamation, have been demanded by the set at 8,101' Mby BOPCO, L.F., stat 3,953'. BOPCO ater. TOC will be luge hole volume a	of all pertinent markers outs shall be filed within a Form 3160-4 shall be completed, and the operation of the planned two stag D. This will negate to suggests a high probact, L.P. shall wait on confirmed with a tend are listed below:	and 30 file ato he ibi	
If the proposal is to deepen dire Attach the Bond under which the following completion of the investing has been completed. Fir determined that the site is ready BOPCO, L.P. respectfully Given the PLU #344H is on job, to a one stage cement for a DV tool. Computer a sucess at circulating cement cement for 18 hrs or until survey after completion of Spacer: 20 bbl of fresh wat Lead: 365 sks Tuned Light Tail: 65 sks HalCem - H (14. Thereby certify that the fore Name (Printed/Typed)	ctionally or recomplete horizonthe work will be performed or provolved operations. If the operational Abandonment Notices shall be for final inspection.) requests the changes listed butside of both the Secretary job, for the 2nd intermediate modeling provided by the cent 500' into the 9-5/8", 40 pp 500 psi compressive strength cement job. Updated cement job. Updated cementer with red dye er at Cement + 0.75 lb/sk CFR-15.6 ppg, 1.19 cu ft/sk, 5.39 pick complexity in the complex com	rtinent details, including es ally, give subsurface location of the Bond No. on file on results in a multiple combe filed only after all require below to be approved for sand R-111 Potash arte 7", 26 ppf, N-80, LTC ment company, based of J. J-55, LTC casing shoth has been reached, whent volumes are based of the same	timated starting date of ons and measured and with BLM/BIA. Recupletion or recompletic ements, including record the above caption at the above caption and approvided to be which will be settichever time is grean 50% excess of gas to blook Poly-E-Flak	of any proposed work of true vertical depths quired subsequent repon in a new interval, lamation, have been demanded by the set at 8,101' Mby BOPCO, L.F., stat 3,953'. BOPCO ater. TOC will be luge hole volume a	of all pertinent markers outs shall be filed within a Form 3160-4 shall be completed, and the operation of the planned two stag D. This will negate to suggests a high probact, L.P. shall wait on confirmed with a tend are listed below:	and 3(file ato he ibi	
If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Fir determined that the site is ready BOPCO, L.P. respectfully Given the PLU #344H is on job, to a one stage cement for a DV tool. Computer a sucess at circulating cement cement for 18 hrs or until survey after completion of Spacer: 20 bbl of fresh wat Lead: 365 sks Tuned Ligh Tail: 65 sks HalCem - H (ctionally or recomplete horizonthe work will be performed or provolved operations. If the operational Abandonment Notices shall be for final inspection.) requests the changes listed butside of both the Secretary job, for the 2nd intermediate modeling provided by the cent 500' into the 9-5/8", 40 pp 500 psi compressive strength cement job. Updated cement job. Updated cementer with red dye er at Cement + 0.75 lb/sk CFR-15.6 ppg, 1.19 cu ft/sk, 5.39 pick complexity in the complex com	rtinent details, including es ally, give subsurface location of the Bond No. on file on results in a multiple combe filed only after all require below to be approved for sand R-111 Potash arte 7", 26 ppf, N-80, LTC ment company, based of J. J-55, LTC casing shoth has been reached, whent volumes are based of the same	timated starting date of ons and measured and with BLM/BIA. Recupletion or recompletic ements, including record the above caption ea, BOPCO, L.P. recording which will be input provided by which will be set ichever time is green 50% excess of gas bl/sk Poly-E-Flak	of any proposed work of true vertical depths quired subsequent repon in a new interval, lamation, have been dependent of the set at 8,101° M by BOPCO, L.P., stat 3,953°. BOPC atter. TOC will be tauge hole volume a	of all pertinent markers outs shall be filed within a Form 3160-4 shall be completed, and the operation of the planned two stages. This will negate the suggests a high probact of the planned with a tend are listed below: ROVED	and 3(file ato he ibi	
If the proposal is to deepen dire Attach the Bond under which the following completion of the investing has been completed. Fir determined that the site is ready BOPCO, L.P. respectfully Given the PLU #344H is on job, to a one stage cement for a DV tool. Computer a sucess at circulating cement cement for 18 hrs or until survey after completion of Spacer: 20 bbl of fresh wat Lead: 365 sks Tuned Light Tail: 65 sks HalCem - H (14. Thereby certify that the fore Name (Printed/Typed)	ctionally or recomplete horizonthe work will be performed or provolved operations. If the operational Abandonment Notices shall be for final inspection.) requests the changes listed lutside of both the Secretary job, for the 2nd intermediat modeling provided by the cent 500' into the 9-5/8", 40 pp 500 psi compressive strengticement job. Updated cementer with red dye er at Cement + 0.75 lb/sk CFR-15.6 ppg, 1.19 cu ft/sk, 5.39 points true and correct see	rtinent details, including es ally, give subsurface location of the Bond No. on file on results in a multiple combe filed only after all require below to be approved for the 7", 26 ppf, N-80, LTC casing shoth has been reached, when the volumes are based of the theory	timated starting date of one and measured and with BLM/BIA. Recupletion or recompletic ements, including record the above caption of the above caption of the above caption of the above caption input provided by the which will be set inchever time is green 50% excess of gas in 50% e	of any proposed work of true vertical depths quired subsequent repon in a new interval, lamation, have been dependent to the control of the c	of all pertinent markers outs shall be filed within a Form 3160-4 shall be completed, and the oper the planned two stag D. This will negate 1 suggests a high probact of the planned with a tend are listed below: ROVED 1 4 2012 1 7 2012 1 1 2012	and 30 file ato	
If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Fir determined that the site is ready BOPCO, L.P. respectfully Given the PLU #344H is on job, to a one stage cement for a DV tool. Computer is success at circulating cement cement for 18 hrs or until survey after completion of Spacer: 20 bbl of fresh wat Lead: 365 sks Tuned Light Tail: 65 sks HalCem - H (14. Thereby certify that the fore, Name (Printed/Typed) Christopher Gies	ctionally or recomplete horizonthe work will be performed or provolved operations. If the operational Abandonment Notices shall be for final inspection.) requests the changes listed butside of both the Secretary job, for the 2nd intermediate modeling provided by the cent 500' into the 9-5/8", 40 pp 500 psi compressive strength cement job. Updated cement job. Updated cementer with red dye er at Cement + 0.75 lb/sk CFR-15.6 ppg, 1.19 cu ft/sk, 5.39 pick complexity in the complex com	rtinent details, including es ally, give subsurface location of the Bond No. on file on results in a multiple combe filed only after all require below to be approved for the 7", 26 ppf, N-80, LTC casing shoth has been reached, when the volumes are based of the theory	timated starting date of one and measured and with BLM/BIA. Recupletion or recompletic ements, including record the above caption of the above caption of the above caption of the above caption input provided by the which will be set inchever time is green 50% excess of gas in 50% e	of any proposed work of true vertical depths quired subsequent repon in a new interval, lamation, have been dependent to the control of the c	of all pertinent markers outs shall be filed within a Form 3160-4 shall be completed, and the oper the planned two stag D. This will negate 1 suggests a high probact of the planned with a tend are listed below: ROVED 1 4 2012 1 7 2012 1 1 2012	and 3(file ato	
If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Fir determined that the site is ready BOPCO, L.P. respectfully Given the PLU #344H is on job, to a one stage cement for a DV tool. Computer is success at circulating cement cement for 18 hrs or until survey after completion of Spacer: 20 bbl of fresh wat Lead: 365 sks Tuned Light Tail: 65 sks HalCem - H (14. Thereby certify that the fore, Name (Printed/Typed) Christopher Gies	ctionally or recomplete horizonthe work will be performed or provolved operations. If the operational Abandonment Notices shall be for final inspection.) requests the changes listed lutside of both the Secretary job, for the 2nd intermediat modeling provided by the cent 500' into the 9-5/8", 40 pp 500 psi compressive strengticement job. Updated cementer with red dye er at Cement + 0.75 lb/sk CFR-15.6 ppg, 1.19 cu ft/sk, 5.39 points true and correct see	rtinent details, including es ally, give subsurface location of the Bond No. on file on results in a multiple combe filed only after all requirible below to be approved for and R-111 Potash are the 7", 26 ppf, N-80, LTC casing she has been reached, when the volumes are based of the total potation of the tot	timated starting date of one and measured and with BLM/BIA. Recupletion or recompletic ements, including record the above caption of the above caption of the above caption of the above caption input provided by the which will be set inchever time is green 50% excess of gas in 50% e	of any proposed work of true vertical depths quired subsequent repon in a new interval, lamation, have been dependent to the control of the c	of all pertinent markers forts shall be filed within a Form 3160-4 shall be completed, and the oper the planned two stag D. This will negate 1 suggests a high probact of the planned with a tend are listed below: ROVED 1 4 2012 1 7 2012 1 TIS Walls FIELD OFFICE	and 30 file ator	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

which would entitle the applicant to conduct operations thereon.